

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 21 S., R. 7 W.

CHAINS	
	T 21 S R 7 W $\frac{1}{4}$ $\frac{S 18}{S 19}$ 1967
	from which
	A cedar, 17 ins. diam., bears N. 60° W., 40 lks. dist., mkd. $\frac{1}{4}$ S18 BT.
	A cedar, 15 ins. diam., bears S. 27° W., 34 lks. dist., mkd. $\frac{1}{4}$ S19 BT.
	Descend 35 ft. over NW. slope.
39.50	Ravine, drains N. 10° E.; asc. 245 ft. over NE. slope.
44.30	Spur ridge, bears N. 20° W. and S. 20° E.; desc. 390 ft. over general W. slope.
58.00	Wet ravine, drains N. 50° W.; asc. 40 ft. over NE. slope.
60.00	Spur, slopes N. 30° W.; desc. 130 ft. over SW. slope.
64.10	Ravine, drains N. 20° E.; asc. 385 ft. over E. slope, changing to NE. slope.
72.49	The cor. of secs. 13, 18, 19 and 24, on the W. Bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap marked and witnessed as described in the official record of the 1952-54 dependent resurvey.
	Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, maple, madrone, chinquapin, alder and yew; undergrowth, vine maple, salal, hazel, arrowwood, huckleberry, vines and ferns.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 1° 41' E., bet. secs. 17 and 18.
	Descend 290 ft. over N. slope, through moderate timber and dense undergrowth.
4.95	Ravine, drains N. 40° W.; asc. 15 ft. over SW. slope.
7.00	Spur, slopes S. 60° W.; desc. 90 ft. over NW. slope.
13.60	Creek, 1 lk. wide, course N. 10° E.; asc. 70 ft. over SE. slope.
18.50	Spur, slopes N. 60° E.; desc. 60 ft. over N. slope.
19.70	Ravine, drains S. 70° E.; asc. 130 ft. over S. slope.
24.00	Spur, slopes E.; desc. 200 ft. over NE. slope.
32.80	Halfway Creek, 15 lks. wide, course NW.; asc. 45 ft. over S. slope.
35.50	Spur, slopes W.; desc. 15 ft. over N. slope.
36.49	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam, 21 ins. in the ground with brass cap marked