

County Surveyor's Record, Douglas County, Oregon

T. 24 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

The history of surveys of township 24 south, range 2 west, Willamette Meridian, Oregon, in the portion covered by this resurvey is as follows:

The east boundary of the township was surveyed by John A. McQuinn in 1883, as shown on the official plat of survey approved January 17, 1895. In 1896 Winfield S. Chapman and Carl S. Nicklin retraced the east boundary of the township and surveyed the subdivisional lines of township 24 south, range 1 west, closing against the McQuinn line as shown on the official plat of survey approved August 10, 1897. In 1951 Levi E. Tallett dependently resurveyed the east boundary of section 36, as shown on the official plat of survey accepted November 2, 1964.

Preliminary to the resurvey the lines of the original surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only lines bounding, or crossing, public lands were blazed. All lines were measured twice.

The directions of lines were determined by the solar transit method.

The geographic position of the southeast corner of section 25, as scaled from the Mace Mountain quadrangle map, published by the United States Geological Survey, in 1955, is as follows:

Latitude 43° 27.3' N. Longitude 122° 52.5' W.

The mean magnetic declination is 19° 07' E.

Dependent Resurvey, Portion of E. Bdy.,
T. 24 S., R. 2 W., Willamette Meridian, Oregon

(Restoring the 1883 survey by John A. McQuinn,
the 1896 retracement by Chapman and Nicklin, and
the 1951 dependent resurvey by Levi E. Tallett)

From the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., determined at record bearing and distance from the remaining orig. bearing tree mkd. by McQuinn:

A cedar, 44 ins. diam., bears N. 40° E., 52 lks. dist., with scribe marks S20 T24 BT visible on partially healed blaze.

and the remaining bearing tree mkd by Tallett:

A sawed cedar stump, 40 ins. diam., bears S. 32° W., 122 lks. dist., with scribe marks T24S R2W S36 BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S	T 24 S
S 25	R 1 W
S 36	S 30
R 2 W	
	1967