

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 24 S., R. 2 W.

CHAINS

from which a new bearing tree

A cedar, 65 ins. diam., bears N.  $50\frac{1}{2}^{\circ}$  W., 135 lks. dist., mkd.  
T24S R2W S25 BT.

The corner is located at the NE. cor. of a logged area, and in the W. edge of a creek, 6 lks. wide, filled with logging debris, course N.  $35^{\circ}$  W.

N.  $0^{\circ} 28'$  W., on the E. bdy. of sec. 25, marking and blazing the true line.

Ascend 115 ft. over SW. slope, through heavy timber and moderate undergrowth.

- 7.10 Top of ascent, slopes W.; desc. 290 ft. over NW. slope.
- 26.25 Bottom of descent, slopes W.; asc. 100 ft. along W. slope.
- 34.00 Top of ascent, slopes W.; des. 70 ft. along W. slope across a rocky barren.
- 39.58 Point for the  $\frac{1}{4}$  sec. cor. of sec. 25 only, restored by the method of irregular boundaries at proportionate position; there is no remaining evidence of the original corner.
- Set an iron post, 12 ins. long, 1 in. diam., 3 ins. into a drill hole in solid rock, with brass cap mkd.

T 24 S |  
 $\frac{1}{4}$  S 25 |  
 R 2 W |  
 1967

from which

A fir, 33 ins. diam., bears S.  $66\frac{1}{2}^{\circ}$  W.,  $71\frac{1}{2}$  lks. dist. mkd.  
 $\frac{1}{4}$  S25 BT.

A fir, 30 ins. diam., bears N.  $45^{\circ}$  W.,  $66\frac{1}{2}$  lks. dist. mkd.  
 $\frac{1}{4}$  S25 BT.

The corner falls on a rock outcropping facing W.

N.  $6^{\circ} 50'$  E., beginning new measurement.

Descend 35 ft. along rocky W. slope.

- 1.00 Leave rocky barren, edge bears N.  $20^{\circ}$  E. and S.  $20^{\circ}$  W.; desc. 100 ft. over steep, rocky, NW. slope.
- 4.70 Creek, 10 lks. wide, course W.; from SE.; asc. 140 ft. over SW. slope.
- 10.75 Spur, slopes W.; desc. 25 ft. along rocky W. slope.
- 18.10 Spur, slopes NW.; desc. 215 ft. over NW. slope.
- 24.00 Northeast fork of Rock Creek, 50 lks. wide, course SW.; asc. 145 ft. over SE. slope.
- 29.91 From this point the orig. closing cor. of secs. 19 and 30, T. 24 S., R. 1 W., bears East, 0.07 chs. dist., perpetuated and recorded by Bruce A. Shaner, Registered Land Surveyor, in 1965, and again perpetuated and recorded by the Douglas County Surveyor, in 1966, monumented with an iron post, 1 in. diam., protruding 10 ins. above ground, firmly set, with brass cap mkd.