

## County Surveyor's Record, Douglas County, Oregon

T. 26 S., R. 8 W., Willamette Meridian, Oregon

## CHAINS

The history of surveys of that portion of township 26 south, range 8 west, Willamette Meridian, Oregon, covered by this resurvey, is as follows:

In 1881 Addison R. and Samuel C. Flint surveyed the boundaries of the township as shown on the official plat of survey approved January 14, 1882. In 1896 John W. Meldrum resurveyed the west boundary and destroyed all of the original corners established by the Flint's. In the same year William P. Heydon subdivided the township using Meldrum's corners on the west boundary, as shown on the official plat of survey approved September 10, 1897, and October 29, 1898.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Original corners were remonumented in their original positions. lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only the lines bounding, or crossing, public lands were blazed.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and Special Instructions dated April 26, 1967, for Group No. 638, Oregon.

The directions of lines were determined by the solar compass method.

The geographic position of the southeast corner of section 32, as computed from a direct tie made to United States Coast and Geodetic Survey triangulation station, ELWOODS 1953, is as follows:

Latitude  $43^{\circ} 15' 28.64''$  N. Longitude  $123^{\circ} 39' 49.20''$  W.

The mean magnetic declination is  $19^{\circ} 24'$  E.

Dependent Resurvey of a Portion of the S. Bdy.,  
T. 26 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the 1881 survey by Addison R. and  
Samuel C. Flint and the 1896 resurvey  
by William P. Heydon)

The cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., determined at record distance from the remaining bearing trees marked by Heydon:

A rotted fir stump, 30 ins. diam., bears N.  $20^{\circ}$  E., 48 lks. dist., with old axe marks visible on decayed blaze. (Record N.  $2^{\circ}$  E.)

A fir snag, 45 ins. diam., bears S.  $38^{\circ}$  E., 215 lks. dist., with fragmentary scribe marks visible on decayed blaze.

A fir snag, 50 ins. diam., bears S.  $61^{\circ}$  W., 315 lks. dist., with no marks remaining.

and trees for which I have no record

A fir, 60 ins. diam., bears N.  $10^{\circ}$  E., 225 lks. dist., with scribe marks S33 T26 R8W visible on weathered bark blaze.

A fir, 52 ins. diam., bears S.  $84^{\circ}$  W., 291 lks. dist., with scribe marks T27S R8W visible on weathered bark blaze.

At the corner point