

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the S. Bdy., T. 26 S., R. 8 W.

CHAINS

at the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.

T 26 S R 8 W
S 31 S 32
S 6 S 5
T 27 S
1967

from which new bearing trees

A hemlock, 16 ins. diam., bears N. 58° E., 91 lks. dist., mkd.
T26S R8W S32 BT.A hemlock, 7 ins. diam., bears S. 44° E., 31 lks. dist., mkd.
T27S R8W S5 BT.A hemlock, 6 ins. diam., bears N. 55° W., 58 lks. dist., mkd.
T T26S R8W S31 BT.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, yew, madrone, and alder; undergrowth, vine maple, huckleberry, thimbleberry, arrowwood, hazel, salal, Oregon grape, and fern.

Dependent Resurvey of a Portion of the W. Bdy.,
T. 26 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the 1896 survey by John W. Meldrum)

The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of T. 26 S., R. 8 W., determined at record bearing and distance from the remaining original bearing trees:

A rotted and burned fir stump, 18 ins. diam., bears S. 18° E., 61 lks. dist., with no marks remaining.

A fir snag, 32 ins. diam., bears S. 85° W., 358 lks. dist., with no marks visible on opened and rotted blaze.

and bearing trees marked and recorded by Arthur Boyer, Registered Engineer, in 1959:

A fir, 20 ins. diam., bears N. 78° E., 6 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.

A fir, 15 ins. diam., bears S. 34° E., 30 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.

A fir, 25 ins. diam., bears S. 35° W., 39 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.

A fir, 28 ins. diam., bears N. 65° W., 12 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.