

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines. T. 26 S., R. 8 W.

CHAINS

At the corner point

Set a fiberglass post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ S\ 32\ | S\ 33 \\ T\ 26\ S\ R\ 8\ W \\ 1967 \end{array}$$

from which new bearing trees

A fir, 14 ins. diam., bears S. 63° E., 56 lks. dist., mkd. $\frac{1}{4}$ S33 BT.A fir, 11 ins. diam., bears N. 31° W., 58 lks. dist., mkd. $\frac{1}{4}$ S32 BT.

Deposit the iron pipe alongside the fiberglass post.

N. 0° 24' E., beginning new measurement:

Descend 300 ft. over NW. slope.

13.90 Ravine, drains W.; asc. 20 ft. over SW. slope.

20.355 Point for the N 1/16 sec. cor. of secs. 32 and 33. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} N\ 1/16 \\ S\ 32\ | S\ 33 \\ 1967 \end{array}$$

from which

A fir, 14 ins. diam., bears N. 46° E., 20 lks. dist. mkd. N. 1/16 S33 BT.

A fir, 13 ins. diam., bears S. 15° W., 15 lks. dist., mkd. N 1/16 S32 BT.

Ascend 25 ft. over SW. slope.

23.40 Top of ascent, slopes W.; desc. 35 ft. over NW. slope.

30.25 Spur, slopes N. 20° W.; desc. 270 ft. over NE. slope.

40.71 The cor. of secs. 28, 29, 32, and 33, perpetuated and recorded by Marvin C. Ramsey, Registered Land Surveyor, in 1960, with an iron pipe, 36 ins. long, 2 ins. diam., firmly set 28 ins. in the ground, from which the only remaining original bearing tree:

A rotted fir stump, 16 ins. diam., bears N. 50° E., 4 lks. dist. with fragmentary scribe marks visible on opened blaze.

and trees marked by Ramsey

A fir, 8 ins. diam., bears N. 64° E., 11 lks. dist., with scribe marks T26S R8W S28 RS404 BT visible on partially healed blaze.

A fir, 18 ins. diam., bears S. 10° E., 21½ lks. dist., with healed blaze.

A fir, 10 ins. diam., bears S. 77° W., 9 lks. dist., with scribe marks T26S R8W S32 RS404 BT visible on partially healed blaze.