

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of W. Bdy., T. 26 S., R. 8 W.

CHAINS

A fir, 13 ins. diam., bears N. 33° W., 19 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

T 26 S R 8 W
S 29 | S 28
S 32 | S 33
1967

Deposit the iron pipe alongside the iron post.

Land, Mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, chinquapin, yew, dogwood, and madrone; undergrowth, huckleberry, vine maple, arrowwood, hazel, rhododendron, salmonberry, Oregon grape, salal, and fern.

From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp. N. 0° 37' W., bet. secs. 31 and 32.

Ascend 5 ft. over SE. slope, through heavy timber and light undergrowth.

- 1.35 Ridge, bears E. and W.; desc 235 ft. over N. slope.
- 16.95 Creek, 2 lks. wide, course N. 70° W.; asc. 15 ft. over SW. slope.
- 17.95 Point of spur, slopes W.; desc. 15 ft. over NW. slope.
- 19.60 Fall Creek, 6 lks. wide, course SW.; asc. 160 ft. over SE. slope.
- 40.35 The ¼ sec. cor. of secs. 31 and 32, determined at record distance from the original bearing trees:

A fir snag, 44 ins. diam., bears N. 47° E., 52 lks. dist., with healed blaze. (Record, N. 42° E.)

A hemlock, 14 ins. diam., bears N. 67° W., 23 lks. dist., with scribe marks ¼ S visible on opened blaze. (Record, N. 57° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

¼
S 31 | S 32
T 26 S R 8 W
1967

from which new bearing trees

A hemlock, 14 ins. diam., bears S. 50° E., 40 lks. dist., mkd. ¼ S32 BT.

A hemlock, 15 ins. diam., bears N. 60° W., 57 lks. dist., mkd. ¼ S31 BT.

N. 0° 21' E., beginning new measurement.

Ascend 60 ft. over gradual SE. slope.

- 20.065 Point for the N 1/16 sec. cor. of secs. 31 and 32.