

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 26 S., R. 8 W.

CHAINS

S. 89 58' W., beginning new measurement.

Descend 400 ft. over W. slope, changing to SW. slope.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked

E 1/16 S 30
S 31
1967

from which

A fir, 14 ins. diam., bears N. 50° 18 lks. dist., mkd. E 1/16 S30 BT.

A fir, 12 ins. diam., bears S. 4° E., 23 lks. dist., mkd. E 1/16 S31 BT.

Descend 25 ft. over NW. slope.

23.05 Ravine, drains NE.; asc. 50 ft. over NE. slope.

33.40 Ridge, bears N. and S.; desc. 45 ft. over NW. slope.

35.00 Callahan Road, 35 lks. wide, bears N. and S., turning to SE.

40.54 The 1/4 sec. cor. of secs. 30 and 31, perpetuated and recorded by Arthur Boyer, Registered Engineer, in 1959, with a steel rod, 30 ins. long, 1 in. diam., firmly set 20 ins. in the ground, from which the original bearing trees:

A sawed fir stump, 62 ins. diam., bears N. 68° E., 268 lks. dist., with fragmentary scribe marks visible on opened blaze. (Record, N. 71° E.)

A fir root crown, 20 ins. diam., bears S. 44° E., 354 lks. dist., with no marks remaining.

and trees marked by Boyer

A sawed fir stump, 24 ins. diam., bears N. 44° W., 38 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A fir, 10 ins. diam., bears S. 31° W., 25 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked

1/4 S 30
S 31
T 26 S R 8 W
1967

from which a new bearing tree

A fir, 14 ins. diam., bears N. 75° W., 35 lks. dist., mkd. 1/4 S30 BT.

Deposit the steel rod alongside the iron post.

S. 89° 58' W., beginning new measurement.

Descend 400 ft. over W. slope, changing to SW. slope.

Sec 29 14183

Duplicate

Duplicate