

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 26 S., R. 8 W.

CHAINS

from which

A fir, 10 ins. diam., bears N. 27° E., 32 lks. dist., mkd. $\frac{1}{4}$ S29 BT.

A fir, 14 ins. diam., bears S. 75° W., 31 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S30 BT.

Ascend 10 ft. over SE. slope.

42.90 Spur, slopes E.; desc. 80 ft. over N. slope.

46.50 Creek, 2 lks. wide, course NE.; asc. 240 ft. over SE. slope.

57.90 Spur, slopes N. 80° E.; desc. 540 ft. over NE. slope.

79.20 Creek, 8 lks. wide, course E.; asc. 55 ft. over S. slope.

80.26 The cor. of secs. 19, 20, 29, and 30, determined at record bearing and distance from the only remaining original bearing tree:

A cedar snag, 25 ins. diam., bears S. 52° W., 210 lks. dist., with scribe marks 30 T26S W BT visible on open and burned blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap marked

T 26 S R 8 W	
S 19	S 20
S 30	S 29
1967	

from which new bearing trees

A fir, 22 ins. diam., bears N. 58° E., 25 lks. dist., mkd. T26S R8W S20 BT.

A fir, 20 ins. diam., bears S. 75° E., 65 lks. dist., mkd. T26S R8W S29 BT.

A fir, 18 ins. diam., bears S. 27° W., 14 lks. dist., mkd. T26S R8W S30 BT.

A fir, 22 ins. diam., bears N. 31° W., 21 lks. dist., mkd. T26S R8W S19 BT.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, chinquapin, maple, alder, yew, myrtle, and dogwood; undergrowth, vine maple, huckleberry, salmonberry, thimbleberry, arrowwood, hazel, rhododendron, manzanita, salal, Oregon grape and fern.

S. 89° 11' W., bet. secs. 19 and 30.

Ascend 5 ft. along S. slope, through heavy timber and dense undergrowth.

7.00 Creek, 10 lks. wide, course S. 80° E., turning to E.; asc. 620 ft. over NE. slope, changing to E. slope.

40.46 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked.