

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 30, T. 26 S., R. 8 W.

CHAINS	
62.90	Creek, 2 lks. wide, course N. 80° E.; asc. 140 ft. over SE. slope.
74.70	Top of ascent, slopes E.; desc. 25 ft. over NE. slope.
76.90	Ravine, drains E.; asc. 25 ft. over SE. slope.
79.46	The $\frac{1}{4}$ sec. cor. of secs. 19 and 30.
From the $\frac{1}{4}$ sec. cor. of secs. 29 and 30.	
S. 89° 40' w., on the E. and W. center line of sec. 30.	
Descend 45 ft. over SW. slope, through heavy second growth timber and dense undergrowth.	
3.40	Ravine, drains S.; asc. 225 ft. over SE. slope.
20.23	Point for the center E 1/16 sec. cor. of sec. 30.
Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.	
$\begin{array}{c} \text{C} \frac{\text{E } 1/16}{\text{S } 30} \text{C} \\ 1967 \end{array}$	
from which	
A fir, 9 ins. diam., bears N. 21° W., 12 lks. dist., mkd. CE 1/16 S30 BT.	
A fir, 20 ins. diam., bears S. 50° E., 110 lks. dist., mkd. CE 1/16 S30 BT.	
Ascend 140 ft. over E. slope.	
24.40	Callahan Road, 30 lks. wide, bears N. 40° W. and S. 40° E.
28.00	Ridge, bears N. and S.; desc. 110 ft. over SW. slope.
40.46	The center $\frac{1}{4}$ sec. cor. of sec. 30.
Descend 115 ft. over SW. slope.	
46.70	Creek, 1 lk. wide, course S. 30° W.; asc. 15 ft. over SE. slope.
47.80	Top of ascent, slopes S.; desc. 115 ft. over SW. slope.
60.64	Point for the center W 1/16 sec. cor. of sec. 30.
Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.	
$\begin{array}{c} \text{C} \frac{\text{W } 1/16}{\text{S } 30} \text{C} \\ 1967 \end{array}$	
from which	
A fir, 18 ins. diam., bears N. 25° W., 28 lks. dist., mkd. CW 1/16 S30 BT.	
A fir, 18 ins. diam., bears S. 73° W., 54 lks. dist., mkd. CW 1/16 S30 BT.	
Descend 330 ft. over SW. slope.	
81.03	The $\frac{1}{4}$ sec. cor. of secs. 25 and 30.