

## County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 30, T. 26 S., R. 8 W.

CHAINS

Subdivision of Section 32, T. 26 S., R. 8 W.  
Willamette Meridian, Oregon

From the  $\frac{1}{4}$  sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.  
N.0° 11' E., on the N. and S. center line of sec. 32.

Descend 5 ft. along E. slope, through heavy timber and light under-  
growth.

- 4.30 Creek, 2 lks. wide, course S. 65° E.; asc. 140 ft. over S. slope.  
15.60 Top of ascent, slopes E.; desc. 15 ft. over NE. slope.  
17.60 Ravine, drains S. 50° E.; asc. 80 ft. over SE. slope.  
24.00 Ridge, bears N. 20° E. and S. 20° W.; desc. 60 ft. over NW. slope.  
32.70 Bottom of descent, slopes W.; asc. 10 ft. over SW. slope.  
33.80 Ridge, bears E. and W.; desc. 20 ft. over NE. slope.  
34.65 Callahan Road, 30 lks. wide, bears N. 35° W. and S. 35° E.  
40.35 Point for the center  $\frac{1}{4}$  sec. cor. of sec. 32, at intersection with  
the E. and W. center line.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the  
ground, with brass cap mkd.

C  $\frac{1}{4}$  S 32  
1967

from which

A hemlock, 12 ins. diam., bears N. 50° E., 6 lks. dist., mkd.  
C  $\frac{1}{4}$  S32 BT.

A fir, 15 ins. diam., bears S. 16° W., 7 lks. dist., mkd.  
C  $\frac{1}{4}$  S32 BT.

Descend 380 ft. over NE. slope.

- 60.59 Point for the center N  $\frac{1}{16}$  sec. cor. of sec. 32.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the  
ground, to solid rock, and in a mound of stone, 3 ft. base, to top,  
with brass cap mkd.

C  
N  $\frac{1}{16}$  | S 32  
C  
1967

from which

A cedar, 8 ins. diam., bears N. 71° E., 27 lks. dist., mkd.  
CN  $\frac{1}{16}$  S32 BT.

A fir, 18 ins. diam., bears S. 48° W., 25 lks. dist., mkd.  
CN  $\frac{1}{16}$  S32 BT.

Descend 175 ft. over NE. slope.

- 63.90 Creek, 2 lks. wide, course E.; asc. 250 ft. over SE. slope.  
71.90 Spur, slopes E.; desc. 170 ft. over NE. slope.