

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of South Boundary, T. 27 S., R. 4 W.

CHAINS

and bearing trees mkd. by Byron

A rotted cedar stump, 12 ins. diam., bears N. $44\frac{1}{2}^{\circ}$ E., 184 lks dist., with scribe marks CS BT visible on partially healed double blaze.

A fir, 12 ins. diam., bears S. $56\frac{1}{2}^{\circ}$ E., 115 lks. dist., mkd. with a healed blaze.

A cedar, 15 ins. diam., bears S. $53\frac{1}{2}^{\circ}$ W., 100 lks. dist., with illegible scribe marks visible on partially healed blaze.

A fir, 35 ins. diam., bears N. 79° W., 56 lks. dist., with illegible scribe marks visible on partially healed blaze.

and a bearing tree mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1964

A fir, 9 ins. diam., bears N. $57\frac{1}{4}^{\circ}$ E., 151 lks. dist., with illegible scribe marks visible on partially healed double blaze.

From this point the NE. cor. of Donation Land Claim No. 52 T. 27 S. R. 4 W., bears N. $65^{\circ} 29'$ E., 7.485 chs. dist., perpetuated and recorded by F. C. Frear, Deputy County Surveyor, in 1918, from original corner evidence which is no longer in existence, monumented with an iron pipe, $\frac{1}{2}$ in. diam., protruding 6 ins. above ground, firmly set, from which bearing trees mkd. by Milo E. Godfrey, Deputy County Surveyor in 1959:

An oak, 12 ins. diam., bears N. 46° E., 107 lks. dist., with scribe marks NE DLC#52 CS BT visible on partially healed double blaze.

A cedar, 13 ins. diam., bears S. 38° W., 122 lks. dist., with scribe marks NE DLC#52 CS BT visible on partially healed double blaze.

N. $89^{\circ} 34'$ W., bet. secs. 5 and 32 marking the true line.

Descend 25 ft. over SW. slope, through medium timber and moderate undergrowth, across partially logged area.

- 2.00 Bottom of descent, drains S.; asc. 65 ft. over SE. slope.
- 5.50 Top of ascent, slopes S.; desc. 25 ft. over SW. slope.
- 7.00 Bottom of descent, drains S.; asc. 155 ft. over broken SE. slope.
- 18.40 Spur, slopes SW.; desc. 120 ft. over NW. slope.
- 24.90 Bottom of descent, drains N.; asc. 15 ft. over NE. slope.
- 29.20 Top of ascent, slopes N.; desc. 125 ft. over NW. slope.
- 39.135 Point for the $\frac{1}{4}$ sec. cor of sec. 5 only, on the N. bdy. of T. 28 S. R. 4 W., hereinafter described.
- Descend 3 ft. along N. slope.
- 39.32 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 32 only, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C
T 27 S R 4 W
 $\frac{1}{4}$ S 32
1967