

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Poirton of South Boundary, T. 27 S., R. 4 W.

## CHAINS

from which

A fir, 35 ins. diam., bears N.  $55\frac{1}{2}^{\circ}$  E., 247 lks. dist., mkd.  
 $\frac{1}{4}$  S32 BT.

A fir, 15 ins. diam. bears N.  $31\frac{3}{4}^{\circ}$  W.,  $43\frac{1}{2}$  lks. dist., mkd.  
 $\frac{1}{4}$  S32 BT.

From this point an original bearing tree now displaced by road construction, bears N.  $63\frac{1}{2}^{\circ}$  W., 33 lks. dist., an uprooted fir, 18 ins. diam., with faint scribe marks S BT visible on bark. There is no evidence remaining of the original position of this tree.

Descend 140 ft. over NW. slope.

- 39.63 An abandoned dirt road, 10 lks. wide, bears NE. and SW.
- 50.00 An abandoned dirt road, 10 lks. wide, bears NE. and SW.
- 53.07 Wire fence, bears NE. and SW.; enter open field.
- 54.95 Wire fence, bears NE. and SW.; leave field.
- 55.15 Creek, 2 lks. wide, course SW.; asc. 160 ft. along S. slope, changing to SE. slope.
- 68.50 Top of ascent, slopes S.; desc. 200 ft. over SW. slope.
- 72.85 From this point the corner of wire fences which extend N., S., and W., bears North, 10 lks. dist. Continue along fence.
- 78.27 True point for the closing cor. of secs. 5 and 6, on the N. bdy. of T. 28 S., R. 4 W., hereinafter described. This point falls at the corner of wire fences which extend N. and E.
- Descend 7 ft. over W. slope.
- 78.50 Gravelled road, 20 lks. wide, bears NW. and SE., curving to S.
- 78.70 The cor. of wire fences extending S. and W.
- 78.98 The standard cor. of secs. 31 and 32 only, perpetuated and recorded by F. C. Frear, County Surveyor, in 1921, monumented with an iron wagon boxing, 2 x 12 ins., protruding 1 in. above ground, firmly set, at record bearing and distance from the remaining original bearing tree:
- A cedar, 27 ins. diam., bears S.  $28^{\circ}$  E., 17 lks. dist., with a healed blaze.
- and a bearing tree mkd. by Frear in 1921
- An uprooted cedar, 26 ins. diam., bears S.  $82^{\circ}$  W., 43 lks. dist., with a healed blaze.
- and bearing trees mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1963
- A cedar, 10 ins. diam., bears N.  $75\frac{1}{2}^{\circ}$  E., 87 lks. dist., with scribe marks T27S R4W S32 CS BT visible on partially healed blaze.
- A cedar, 11 ins. diam., bears N.  $38\frac{1}{4}^{\circ}$  W.,  $129\frac{1}{2}$  lks. dist., with scribe marks T27S R4W S31 CS BT visible on partially healed blaze.
- At the corner point
- Set a fiberglas post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.