

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of South Boundary, T. 27 S., R. 4 W.

CHAINS

S C
T 27 S R 4 W
S 31 | S 32
S 6

T 28 S R 4 W
1967

Reset the wagon boxing alongside the fiberglass post.

Land, mountainous.

Soil, clay.

Timber, fir, oak, hemlock, cedar, maple, yew, madrone, cascara, alder, ash, willow, and myrtle; undergrowth, fern, salal, poison oak, vine maple, blackberry, hazel, wild rose, arrowwood, and young timber.

Dependent Resurvey, Portion of Subdivisional Lines,
T. 28 S., R. 4 W., Willamette Meridian, Oregon

(Restoring the 1856 survey by Aaron Bowser, the 1881
survey by William H. Byars, and the 1958 resurvey by
Irving Zirpel, Jr., and William W. Glenn)

From the cor. of secs. 4, 5, 8, and 9, remonumented by Zirpel and Glenn in 1958, with an iron post, 2½ ins. diam., protruding 4 ins. above ground, firmly set, with brass cap mkd.

T 28 S R 4 W
S 5 | S 4
S 8 | S 9
1958

from which the remaining original bearing trees

A sawed fir stump, 10 ft. high, 21 ins. diam., bears S. 70° E. 14 lks. dist., with cruiser marks visible.

An oak, 10 ins. diam., bears N. 5¼° W., 40½ lks. dist., with no scribe marks visible on opened and rotted upper blaze and BT visible on opened lower blaze. (Record, N. 40° W., 7 lks.)

and bearing trees mkd. by Zirpel and Glenn

A fir, 9 ins. diam., bears N. 35 ¾° E., 33 lks. dist., with a healed blaze.

An uprooted fir, 30 ins. diam., bears S. 46° E., 43 lks. dist., with scribe marks T28S R4W S9 BT visible on partially healed blaze.

A cedar, 12 ins. diam., bears S. 3° W., 119 lks. dist., with scribe marks T28S R4W S8 BT visible on partially healed blaze.

A fir, 10 ins. diam., bears N. 60° W., 19 lks. dist., with scribe marks T28S R4W S5 BT visible on partially opened blaze.

and a new bearing tree

A fir, 21 ins. diam., bears S. 51½° E., 95 lks. dist., mkd. T28S R4W S9 BT.

From this point the cor. of wire fences which extend W. and S. 20° E., bending to E., bears N. 3° W., 33½ lks. dist.