

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS

N. 1° 24' W., bet secs. 4 and 5, marking and blazing the true line.

Ascend 10 ft. over SW. slope, through heavy timber and dense undergrowth, along W. edge of logged area.

1.10 Small ravine, drains SW.; asc. 45 ft. over SE. slope.

4.30 Spur, slopes SW.; desc. 15 ft. over NW. slope.

6.90 Bottom of descent, drains W.; asc. 5 ft. over SW. slope.

8.90 Spur, slopes W.; desc. 65 ft. over NW. slope.

11.50 Dry bed of creek, 4 lks. wide, course S. 70° W.; asc. 45 ft. over SW. slope.

18.00 Top of ascent, slopes W.; desc. 5 ft. along W. slope.

18.50 Creek, 1 lk. wide, course S. 20° W.; asc. 15 ft. over S. slope.

20.045 Point for the S 1/16 sec. cor. of secs. 4 and 5.

Set an iron post, 28 ins. long, 2½ ins. diam.; 24 ins. in the ground, with brass cap mkd.

S 1/16  
S 5 | S 4  
1967MARK SMALLEY  
5/9/2006  
C.S. FILE 65/60-5  
Fd. 2 BTS

from which

A fir, 12 ins. diam., bears N. 86° E., 17 lks. dist., mkd.  
S 1/16 S4 BT.A fir, 28 ins. diam., bears S. 65 3/4° W., 71 lks. dist., mkd.  
S 1/16 S5 BT.

Ascend 100 ft. over S. slope, changing to SW. slope.

20.75 Abandoned dirt road, 15 lks. wide, bears E. and W.

25.00 Spur, slopes SW.; desc. 65 ft. over NW. slope.

29.50 Bottom of descent, slopes W.; asc. 30 ft. over SW. slope.

32.50 Dirt road, 15 lks. wide, bears N. 55° W. and SE.

33.50 Rocky spur, slopes N. 70° W.; desc. 120 ft. over N. slope.

40.09 The ¼ sec. cor. of secs. 4 and 5, occupied by the remains of the original corner tree, a sawed and rotted fir stump, 32 ins. diam., with no marks remaining; from which the original bearing trees:

A sawed and rotted fir stump, 30 ins. diam., bears N. 45° E.,  
10½ lks. dist., with no marks remaining. (Record, 8 lks.)A burned and rotted fir stump, 24 ins. diam., bears S. 45° W.,  
10 lks. dist., with no marks remaining. (Record, 7 lks.)

At the corner point

Drive an iron post, 24 ins. long, 1 in. diam., 23 ins. into the center of the stump of the corner tree, with brass cap mkd.

T 28 S R 4 W  
¼  
S 5 | S 4  
1967

from which new bearing trees