

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS

T 28 S R 4 W

$$\begin{array}{c} \frac{1}{4} \\ S 6 | S 5 \\ 1967 \end{array}$$

from which

A fir, 16 ins. diam., bears N. $67 \frac{3}{4}^{\circ}$ E., 236 lks. dist.,
mkd. $\frac{1}{4}$ S5 BT.

A madrone, 9 ins. diam., bears S. $40 \frac{3}{4}^{\circ}$ E., 133 lks. dist.,
mkd. $\frac{1}{4}$ S6 BT.

Descend 30 ft. over N. slope.

40.40 Bottom of descent, drains N. 70° W.; asc. 20 ft. over SW. slope.

42.30 Top of ascent, slopes W.; enter timber, edge bears N. and SE.; desc. 225 ft. over NW. slope.

53.80 Creek, 2 lks. wide, course NE.; asc. 40 ft. over SE. slope.

58.17 Point for the N $1/16$ sec. cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, $2 \frac{1}{2}$ ins. diam., 24 ins. in the
ground, with brass cap mkd.

$$\begin{array}{c} N 1/16 \\ S 6 | S 5 \\ 1967 \end{array}$$

from which

A fir, 10 ins. diam., bears N. $61 \frac{1}{2}^{\circ}$ E., 18 lks. dist., mkd.
N $1/16$ S5 BT.

A fir, 8 ins. diam., bears N. 59° W., $23 \frac{1}{2}$ lks. dist., mkd.
N $1/16$ S6 BT.

From this point an iron pipe $\frac{3}{4}$ in. diam., protruding 14 ins.
above ground, firmly set, bears S. $50^{\circ} 17'$ E., 0.673 chs. dist.

Ascend 145 ft. over SE. slope.

65.10 Spur, slopes E.; desc. 290 ft. over steep rocky N. slope.

70.15 Wire fence, bears E. and W.

70.50 Creek, 25 lks. wide, course NW., and a power line, bears NW. and SE.; asc. 15 ft. over gradual SW. slope.

71.00 Wire fence, bears E. and W.

74.25 Gravelled road, 20 lks. wide, bears N. 5° W. and SE., curving to E. continue along E. side of road.

78.91 Intersect the 6th Standard Parallel South.

True point for the closing cor. of secs. 5 and 6.

Set a fiberglas post, 28 ins. long, $2 \frac{1}{2}$ ins. diam., 24 ins. in the
ground, with brass cap mkd.

$$\begin{array}{c} T 27 S R 4 W \\ S 32 \\ S 6 | S 5 \\ CC \\ T 28 S R 4 W \\ 1967 \end{array}$$