

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS	
	<p>from which</p> <p>A fir, 17 ins. diam., bears S. 35 3/4° E., 48 lks. dist., mkd. T28S R4W S5 CC BT.</p> <p>A cedar, 29 ins. diam., bears S. 47 1/4° W., 61 lks. dist., mkd. T28S R4W S6 CC BT.</p> <p>From this point the original closing cor. of secs. 5 and 6, bears N. 0° 08' W., 0.23 chs. dist., monumented with a concrete filled iron pipe, 1 in. diam., protruding 3 ins. above ground, firmly set, from which the remaining original bearing tree:</p> <p>A sawed and rotted fir stump, 20 ins. diam., bears S. 30° E., 43 lks. dist., with scribe marks BT visible on remaining portion of opened blaze.</p> <p>From this same point, the standard corner of Secs. 31 and 32, hereinafter described, bears N. 89° 34' W., 0.71 chs. dist.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, madrone, oak, maple, ash, myrtle, cedar, alder, and cascara; undergrowth, salal, fern, poison oak, vine maple, hazel, arrowwood, blackberry, and young timber.</p>
0.185	<p>To complete the survey of sec. 5, I return to the standard 1/4 sec. cor. of sec. 32 only, on the S. bdy. of T. 27S., R. 4 W., and run S. 89° 34' E., on the N. bdy. of sec. 5.</p> <p>Point for the 1/4 sec. cor. of sec. 5 only, at midpoint in departure on the N. bdy. of sec. 5.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> 1/4 S 5 T 28 S R 4 W 1967 </p> <p>from which</p> <p>A fir, 21 ins. diam., bears S. 65 1/2° E., 95 lks. dist., mkd. 1/4 S5 BT.</p> <p>A fir, 40 ins. diam., bears S. 9 3/4° W., 228 lks. dist., mkd. 1/4 S5 BT.</p>
	<p>Subdivision of Sec. 5, T. 28 S., R. 4 W.</p>
1.80	<p>From the 1/4 sec. cor. of secs. 5 and 8.</p> <p>N. 1° 01' W., on the N. and S. center line of sec. 5.</p> <p>Ascend 15 ft. over SE. slope, through heavy timber and moderate undergrowth, along wire fence.</p> <p>Top of ascent, slopes E.; desc. 260 ft. over NE. slope.</p>
13.00	<p>Head of ravine, drains NE.; desc. 90 ft. over NE. slope.</p>
20.675	<p>Point for the center S 1/16 sec. cor. of sec. 5.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>