

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 5, T. 28 S., R. 4 W.

CHAINS

$$\begin{array}{c} C \\ S \ 1/16 \ S \ 5 \\ C \\ 1967 \end{array}$$

from which

A fir, 12 ins. diam., bears N.  $70\frac{1}{2}^\circ$  E., 31 lks. dist., mkd. CS  $1/16$  S5 BT.

A fir, 9 ins. diam., bears S.  $40^\circ$  W., 18 lks. dist., mkd. CS  $1/16$  S5 BT.

Descend 110 ft. over N. slope.

22.75 Gravelled road, 20 lks. wide, bears N.  $75^\circ$  W. and SE., curving to S. enter open pasture land.

27.25 Creek, 3 lks. wide, course N.  $60^\circ$  E.; asc. 8 ft. along gradual E. slope.

37.00 Same road, bears N.  $15^\circ$  E. and S.  $15^\circ$  W.; enter scattering timber and dense undergrowth.

41.35 Point for the center  $\frac{1}{4}$  sec. cor. of sec. 5, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} C \ \frac{1}{4} \ S \ 5 \\ 1967 \end{array}$$

from which

A fir, 8 ins. diam., bears S.  $11\frac{1}{2}^\circ$  E., 30 lks. dist., mkd. C  $\frac{1}{4}$  S5 BT.

A fir, 37 ins. diam., bears N.  $9\frac{1}{2}^\circ$  W.,  $34\frac{1}{2}$  lks. dist., mkd. C  $\frac{1}{4}$  S5 BT.

Descend 40 ft. over NE slope.

44.40 Gravelled road, 20 lks. wide, bears N.  $15^\circ$  W. and S.  $15^\circ$  E.; enter open pasture land.

45.765 Intersect the S. bdy. of the Thomas Ledgerwood Donation Land Claim No. 37.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} C \ 37 \\ C \\ \hline CC \ S \ 5 \\ C \\ 1967 \end{array}$$

MARK SMALLEY  
5/9/2006  
C.S. FILE 65/60-8  
Fd. 2 BTS  
1 NEW BT

from which

A fir, 16 ins. diam., bears S.  $17\frac{1}{2}^\circ$  E.,  $46\frac{1}{2}$  lks. dist., mkd. CC S5 BT.

A fir, 26 ins. diam., bears S.  $53^\circ$  W., 96 lks. dist., mkd. CC S5 BT.

From this point the SE. cor of the Thomas Ledgerwood Donation Land Claim No. 37, bears S.  $89^\circ 48'$  E., 45.375 chs. dist., perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1961, monumented with an iron post, 2 ins. diam., protruding 10 ins. above ground, firmly set, with brass cap mkd.