

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the E. Bdy., T. 21 S., R. 9 W.

CHAINS

and new bearing trees

A fir, 5 ins. diam., bears N. $56\frac{1}{2}^\circ$ E., 92 lks. dist., mkd. $\frac{1}{4}$ S7 BT.

A maple, 6 ins. diam., bears S. 83° E., 50 lks. dist., mkd. $\frac{1}{4}$ S7 BT.

N. $0^\circ 16'$ E., beginning new measurement.

Ascend 4 ft. over SE. slope.

0.50 Spur, slopes N. 80° E.; desc. 230 ft. over NE. slope.

4.85 Ravine, drains N. 60° E.; asc. 10 ft. over SE. slope.

6.00 Spur, slopes N. 60° E.; desc. 85 ft. over NE. slope.

8.15 Creek, 3 lks. wide, course S. 65° E.; asc. 685 ft. over broken S. slope.

28.70 Ridge, bears E. and W.; desc. 390 ft. over N. slope.

36.82 The closing cor. of secs. 1 and 12, T. 21 S., R. 9 W., monumented with an iron post, 2 ins. diam., extending 14 ins. above ground, firmly set, with brass cap marked

T 21 S T 21 S
 CC $\frac{S 1}{S 12}$ | S 7
 R 9 W | R 8 W
 1945

from which the remaining original bearing trees

A fir, 42 ins. diam., bears N. 76° E., 12 lks. dist., with healed blaze.

A sawed fir stump, 18 ins. diam., bears S. $64\frac{1}{2}^\circ$ W., 37 lks. dist., with healed blaze

and bearing trees marked in 1945

A burned fir stump, 30 ins. diam., bears S. $70\frac{1}{4}^\circ$ W., 46 lks. dist., with no marks remaining.

A sawed fir stump, 31 ins. diam., bears N. $39\frac{3}{4}^\circ$ W., 67 lks. dist., with healed blaze.

Raise a mound of stone, 4 ft. base, 2 ft. high, West of the corner.

Descend 40 ft. over NE. slope.

38.19 The cor. of secs. 6 and 7 only, T. 21 S., R. 8 W., determined at record bearing and distance from a bearing tree marked in 1945

A fir, 25 ins. diam., bears S. $4\frac{1}{2}^\circ$ E., 51 lks. dist., with fragmentary scribe marks visible on partly healed blaze.

and a bearing tree of which I have no record.

A fir, 37 ins. diam., bears N. 77° E., 36 lks. dist., with scribe marks T21S R8W S6 visible on open and burned blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked