

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 21 S., R. 9 W.

CHAINS

T 21 S	T 21 S
R 9 W	S 6
S 1	S 7
	R 8 W
1966	

Land, mountainous.

Soil, sandy loam.

Timber, fir, hemlock, maple, alder, and willow; undergrowth, arrow-wood, thimbleberry, salmonberry, hazel, huckleberry, blackberry, salal, and fern.

N. 1° 22' W., on the W. bdy. of sec. 6, T. 21 S., R. 8 W.

Descend 95 ft. over NE. slope, across logged and burned area through scattering undergrowth.

- 2.90 Ravine, drains N. 40° E.; asc. 115 ft. over SE. slope.
- 8.20 Spur, slopes N. 50° E.; desc. 220 ft. over NE. slope.
- 12.15 Ravine, drains S. 70° E.; asc. 5 ft. over SE. slope.
- 14.50 Spur, slopes S. 70° E.; desc. 25 ft. over NE. slope.
- 15.70 Ravine, drains S. 40° E.; asc. 160 ft. over SE. slope.
- 21.10 Spur, slopes S. 70° E.; desc. 170 ft. over NE. slope.
- 26.85 Ravine, drains E.; asc. 25 ft. over SE. slope.
- 27.60 Spur, slopes S. 70° E.; desc. 15 ft. over NE. slope.
- 29.20 Ravine, drains S. 50° E.; asc. 310 ft. over SE. slope.
- 35.80 Spur, slopes S. 65° E.; desc. 140 ft. over NE. slope.
- 38.93 The $\frac{1}{4}$ sec. cor. of sec. 6 only, T. 21 S., R. 8 W., monumented with an iron post, 1 ins. diam., extending 8 ins. above ground, firmly set, with brass cap marked

$\frac{1}{4}$	S 6
1945	

from which a bearing tree marked in 1945

A fir snag, 26 ins. diam., bears S. 35 $\frac{1}{2}$ ° E.; 122 lks. dist., with no marks visible on opened and burned blaze.

a bearing tree of which I have no record

An alder, 8 ins. diam., bears S. 85° E., 87 lks. dist., with scribe marks $\frac{1}{4}$ S6 BT visible in the bark.

and a new bearing tree

A fir, 5 ins. diam., bears N. 85° E., 45 lks. dist., mkd. $\frac{1}{4}$ S6 BT.

N. 1° 19' W., beginning new measurement.

Descend 20 ft. over NE. slope.

- .85 Ravine, drains E.; asc. 50 ft. over SE. slope.
- 2.36 Point for the $\frac{1}{4}$ sec. cor. of sec. 1 only, T. 21 S., R. 9 W.
- Set a fiber glas post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked