

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 21 S., R. 9 W.

CHAINS

- 10.00 Dirt road, 20 lks. wide, bears N. 20° E. and S. 20° W., in saddle of ridge top; asc. 75 ft. over S. slope, along ridge top.
- 18.50 Top of ascent on ridge, bears NW. and S., and spur, slopes N. 30° E.; desc. 555 ft. over broken NW. slope.
- 36.80 Spur, slopes N. 30° W.; desc. 75 ft. over NW. slope.
- 38.30 The closing cor. of Tps. 20 and 21 S., R. 9 W., monumented with an iron post, 3 ins. diam., extending 6 ins. above ground, firmly set, with brass cap marked

| | | |
|---------|--|--------|
| T 20 S | | T 20 S |
| R 9 W | | R 8 W |
| CC S 36 | | S 31 |
| S 1 | | |
| T 21 S | | |
| 1954 | | |

from which bearing trees marked by Tillman in 1954

A fir, 24 ins. diam., bears S. 31¼° W., 55 lks. dist., with fragmentary scribe marks visible on partly healed blaze.

A cedar, 14 ins. diam., bears N. 65° W., 67 lks. dist., with no marks visible on nearly healed blaze.

Descend 50 ft. over NW. slope.

- 39.32 The ¼ sec. cor. of sec. 31 only, T. 20 S., R. 8 W., monumented with an iron post, 1 in. diam., extending 6 ins. above ground, firmly set, with brass cap marked

| | | |
|------|--|------|
| ¼ | | S 31 |
| S 1 | | |
| 1950 | | |

from which bearing trees marked by Tillman in 1950

A fir, 33 ins. diam., bears N. 57° E., 108 lks. dist., with healed blaze.

A hemlock, 25 ins. diam., bears S. 24° E., 59 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky and sandy clay loam.

Timber, fir, hemlock, cedar, maple, myrtle, and alder; undergrowth, arrowwood, huckleberry, vine maple, hazel, salal, and fern.

Dependent Resurvey of a Portion of the West Boundary
T. 21 S., R. 9 W., Willamette Meridian, Oregon

(Restoring the 1894 survey by Alonzo Gesner and the 1919 resurvey by Charles M. Collier and Fred Rodolf)

From the angle point bet. secs. 7 and 12, on the E. bdy. of T. 21 S. R. 10 W., determined at record bearing and distance from the bearing trees marked by Collier and Rodolf in 1919:

A fir, 20 ins. diam., bears N. 20° E., 34 lks. dist., with healed blaze.

A fir, 30 ins. diam., bears N. 63° W., 24 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap marked

| | | |
|------|---|--|
| AP | } | |
| 1966 | | |