

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of W. Bdy., T. 21 S., R. 9 W.

CHAINS

N 0° 46' W., on the E. bdy. of sec. 12, T. 21 S., R. 10 W., marking and blazing the true line.

Ascend 50 ft. over SE. slope, through heavy timber and dense undergrowth.

- 1.50 Spur, slopes S. 40° W.; desc. 85 ft. over NW. slope.
- 5.40 Ravine, drains W.; asc. 40 ft. over SW. slope.
- 8.40 Top of ascent, slopes W.; desc. 60 ft. over NW. slope.
- 10.70 Ravine, drains N. 80° W.; asc. 35 ft. over SW. slope.
- 12.00 Spur, slopes N. 75° W.; desc. 70 ft. over NW. slope.
- 13.60 Ravine, drains W.; asc. 65 ft. over SW. slope.
- 15.20 Spur, slopes W.; desc. 45 ft. over NW. slope.
- 18.90 Ravine, drains S. 70° W.; asc. 45 ft. over SW. slope.
- 20.23 The closing cor. of secs. 6 and 7, T. 21 S., R. 9 W., monumented with an iron post, 2 ins. diam., extending 16 ins. above ground, firmly set, with brass cap marked.

T 21 S
 CC | S 6
 | S 7
 R 10 W | R 9 W
 1918

from which the original bearing trees:

A fir, 65 ins. diam., bears N. 37° E., 108 lks. dist., with healed blaze.

A fir, 67 ins. diam., bears S. 52° E., 153 lks. dist., with healed blaze. (Record, S. 55° E.)

and new bearing trees

A fir, 20 ins. diam., bears N. 83½° E., 46 lks. dist., mkd. T21S R9W S6 CC BT.

A cedar, 6 ins. diam., bears S. 86° E., 78 lks. dist., mkd. T21S R9W S7 CC BT.

This corner became a fixed point and angle point in the line, in 1919.

N. 0° 35' W., beginning new measurement.

Ascend 10 ft. over SW. slope.

- 1.40 Top of ascent, slopes W.; desc. 70 ft. over NW. slope.
- 2.85 Ravine, drains W.; asc. 45 ft. over SW. slope.
- 5.30 Ravine, drains S. 40° W.; asc. 270 ft. over SE. slope.
- 10.85 Ridge, bears N. 65° E. and S. 65° W.; desc. 25 ft. over NW. slope.
- 11.57 The cor. of secs. 1 and 12 only, T. 21 S., R. 10 W., monumented with an iron post, 2 ins. diam., extending 14 ins. above ground, firmly set, with brass cap marked

T 21 S |
 | S 1
 | S 12
 R 10 W |
 1919