

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of W. Bdy., T. 21 S., R. 9 W.

CHAINS

from which the original bearing trees

A fir snag, 24 ins. diam., bears S. 33° W., 65 lks. dist., with healed blaze.

A fir, 43 ins. diam., bears N. 10° W., 43 lks. dist., with healed blaze.

and a new bearing tree

A fir, 20 ins. diam., bears S. 20° W., 102 lks. dist., mkd. T21S R10W S12 BT.

Land, mountainous.

Soil, rocky and sandy clay loam.

Timber, fir, hemlock, cedar, maple, and alder; undergrowth, vine maple, huckleberry, hazel, arrowwood, thimbleberry, salmonberry, salal, Oregon grape, and fern.

Dependent Resurvey of a Portion  
of the North Boundary

T. 21 S., R. 9 W., Willamette Meridian, Oregon

(Restoring the 1877 and 1891 surveys by William Thiel, the 1894 resurvey by Alonzo Gesner, and the 1953 resurvey by Thomas A. Tillman)

From the cor. of secs. 4, 5, 32, and 33 on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., extending 10 ins. above ground, firmly set in a mound of stone, 3 ft. base, to top, with brass cap marked and witnessed as described in the official record of the 1953 resurvey.

S. 89° 14' E., on the S. bdy. of sec. 33, T. 20 S., R. 9 W., marking and blazing the true line.

Ascend 220 ft. over steep SW. slope, through heavy timber and dense undergrowth.

- 4.20 Spur, slopes S. 10° W.; desc. 145 ft. over broken SE. slope.
- 7.55 Ravine, drains S.; asc. 20 ft. over SW. slope.
- 8.50 Top of ascent, slopes S.; desc. 145 ft. over SE. slope.
- 12.70 Ravine, drains S.; asc. 70 ft. over SW. slope.
- 14.75 Top of ascent, slopes S.; desc. 35 ft. over SE. slope.

16.90 Ravine, drains S. 35° W.; asc. 45 ft. over SW. slope.

18.30 Spur, slopes SW.; desc. 8 ft. over SE. slope.

19.085 Point for the W 1/16 sec. cor. of sec. 4 only, T. 21 S., R. 9 W.

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, to solid rock, supported in a mound of stone, 3 ft. base, to top, with brass cap marked

W 1/16 \_\_\_\_\_  
S 4  
1966

from which

A fir, 10 ins. diam., bears S. 23° E., 28 lks. dist., mkd. W 1/16 S4 BT.

A fir, 23 ins. diam., bears S. 72° W., 88 lks. dist., mkd. W 1/16 S4 BT.

*1/17/83  
See O.S. File 67/280  
CORRESPONDENCE FOR PERMITS  
IMPROVEMENT SECTION SUBD.  
W.R.*