

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy., T. 21 S., R. 9 W.

CHAINS	
	A hemlock, 22 ins. diam., bears S. 60° W., 38 lks. dist., mkd. E 1/16 S4 BT.
	Descend 240 ft. over SE. slope, changing to NE. slope.
17.00	Ravine, drains N. 50° E.; asc. 10 ft. over NW. slope.
17.25	Point of spur, slopes NE.; desc. 20 ft. over NE. slope.
17.90	Ravine, drains N. 10° E.; asc. 20 ft. over NW. slope.
18.60	Top of ascent, slopes N.; desc. 5 ft. over NE. slope.
19.985	Point for the E 1/16 sec. cor. of sec. 33 only, T. 20 S., R. 9 W.
	Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap marked
	E <u>1/16 S 33</u> 1966
	from which
	A maple, 24 ins. diam., bears N. 71° E., 40 lks. dist., mkd. E 1/16 S33 BT.
	A hemlock, 28 ins. diam., bears N. 62° W., 22 lks. dist., mkd. E 1/16 S33 BT.
	Descend 25 ft. over NE. slope.
24.00	Top of bluff, bears N. and S.; desc. 95 ft. over E. slope of bluff.
25.60	Vincent Creek, 40 lks. wide, course N.; asc. 140 ft. over W. slope, changing to NW. slope.
27.70	Hard surfaced road, 30 lks. wide, bears N. and S.; enter area of the Osbow Burn.
39.97	The cor. of secs. 33 and 34 only, T. 20 S., R. 9 W., monumented with an iron post, 2 ins. diam., extending 8 ins. above bground, firmly set, marked and witnessed as described in the official record of the 1953 resurvey.
	Land, mountainous. Soil, rocky clay loam. Timber, fir, hemlock, cedar, maple, and alder; undergrowth, vine maple, hazel, arrowwood, huckleberry, salmonberry, salal, Oregon grape, poison oak, and fern.
	N. 89° 28' E., on the S. bdy. of sec. 34, T. 20 S., R. 9 W.
	Ascend 380 ft. over W. slope through heavy burned timber and dense undergrowth.
11.10	Spur, slopes S. 60°W.; asc. 15 ft. over SW. slope.
13.48	True point for the closing cor. of secs. 3 and 4, T. 21 S., R. 9 W., hereinafter described.
	Ascend 125 ft. over SW. slope.
19.55	Spur, slopes N. 65° W.; desc. 140 ft. over NW. slope.
27.20	Ravine, drains N. 55° W.; asc. 320 ft. over SW. slope.
38.05	Spur, slopes S. 35° W.; desc. 5 ft. across flat.
40.03	The ¼ sec. cor. of sec. 34 only, T. 20 S., R. 9 W., monumented with an iron post, 1 in. diam., extending 8 ins. above ground, firmly set, marked and witnessed as described in the official record of the 1953 resurvey.