

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy., T. 21 S., R. 9 W.

CHAINS

S. 89° 49' E., beginning new measurement.

Ascend 35 ft. over SW. slope.

4.60 Spur, slopes SE.; desc. 30 ft. over NE. slope.

7.65 Bottom of descent, slopes S.; asc. 50 ft. over SW. slope.

9.70 Ridge, bears NW. and SE.; desc. 70 ft. over NE. slope.

12.45 Ravine, drains NE.; asc. 5 ft. over NW. slope.

12.57 Point for the $\frac{1}{4}$ sec. cor. of sec. 3 only, T. 21 S., R. 9 W.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked
$$\begin{array}{c} \frac{1}{4} S 3 \\ T 21 S R 9 W \\ 1967 \end{array}$$

from which

An alder, 20 ins. diam., bears S. 61° E., 40 lks. dist., mkd.
 $\frac{1}{4}$ S3 BT.A hemlock, 20 ins. diam., bears S. 3° W., 41 lks. dist., mkd.
 $\frac{1}{4}$ S3 BT.

Ascend 20 ft. over NW. slope.

15.00 Spur, slopes N.; desc. 635 ft. over NE. slope.

41.02 The cor. of secs. 34 and 35 only, T. 20 S., R. 9 W., determined in the center of a stump hole, from which the remaining original bearing trees:

The stump hole, of a fallen maple, 28 ins. diam., bears S. 18° E., 36 lks. dist., with healed blaze.

A stump hole, bears S. 25 $\frac{1}{2}$ ° W., 42 lks. dist. (Record, 40 lks.)

A fir, 75 ins. diam., bears S. 88° W., 75 lks. dist., with healed blaze.

and bearing trees marked by Tillman in 1953.

A cedar, 30 ins. diam., bears N. 44° E., 65 lks. dist., with healed blaze.

A stump hole, bears N. 11° W., 39 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked
$$\begin{array}{c} T 20 S R 9 W \\ S 34 S 35 \\ S 3 \\ T 21 S R 9 W \\ 1967 \end{array}$$

from which a new bearing tree

A fir, 50 ins. diam., bears N. 46° W., 155 lks. dist., mkd.
T20S R9W S34 BT.