

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy., T. 21 S., R. 9 W.

CHAINS

A cedar, 28 ins. diam., bears S. 65° E., 96 lks. dist., mkd.  $\frac{1}{4}$  S2 BT.

A burned fir snag, 25 ins. diam., bears S. 86½° W., 70 lks. dist., mkd.  $\frac{1}{4}$  S2 BT.

Descend 90 ft. over NE. slope.

13.40 Creek, 2 lks. wide, course S. 10° E.; asc. 30 ft. along S. slope.

16.60 Ravine, drains S.; desc. 2 ft. along broken S. slope.

22.70 Creek, 2 lks. wide, course S. 20° W.; asc. 165 ft. over SW. slope.

32.00 Point for the E 1/16 sec. cor. of sec. 2 only, T. 21 S., R. 9 W.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap marked

E 1/16 S 2  
1967

from which

A fir, 24 ins. diam., bears S. 1½° E., 42 lks. dist., mkd. E 1/16 S2 BT.

A fir, 21 ins. diam., bears S. 81° W., 61 lks. dist., mkd. E 1/16 S2 BT.

Ascend 230 ft. over SW. slope.

40.04 The cor. of secs. 35 and 36 only, T. 20 S., R. 9 W., monumented with an iron post, 2 ins. diam., extending 12 ins. above ground, firmly set, with brass cap marked

T 20 S R 9 W  
S 35 | S 36  
T 21 S R 9 W  
S 2  
1954

50 - L.O. ROBERTS  
 2/15/64 - C.S. 58/200  
 M 96-26

from which original bearing trees

A burned fir stump, 38 ins. diam., bears N. 81½° E., 232 lks. dist., with no marks remaining. (Record, N. 81° E.)

A burned fir stump, 50 ins. diam., bears S. 81½° E., 177 lks. dist., with no marks remaining.

A burned alder, 25 ins. diam., bears N. 12° W., 8 lks. dist., with healed blaze.

and bearing trees marked by Tillman in 1954.

A burned hemlock snag, 18 ins. diam., bears N. 53½° E., 33 lks. dist., with healed blaze. (Record, 23 lks.)

A burned hemlock snag, 15 ins. diam., bears N. 18° W., 14 lks. dist., with healed blaze.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, maple, and alder; undergrowth, vine maple, salmonberry, hazel, rhododendron, huckleberry, arrowwood, and salal.