

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy., T. 21 S., R. 9 W.

CHAINS

N. 89° 00' E., on the S. bdy. of sec. 36, T. 20 S., R. 9 W.

Ascend 15 ft. over SW. slope, through heavy burned timber and scattering undergrowth.

2.70 Spur ridge, bears N. 10° E. and S. 10° W.; desc. 280 ft. over E. slope.

9.80 Creek, 2 lks. wide, course S.; asc. 85 ft. over SW. slope.

12.44 The closing cor. of secs. 1 and 2, T. 21 S., R. 9 W., monumented with an iron post, 2 ins. diam., extending 14 ins. above ground, firmly set, with brass cap marked

FD OK 12-90
M III-29

T 20 S R 9 W
S 36
S 2 S 1
T 21 S R 9 W
CC
1954

from which the original bearing trees:

A fir, 63 ins. diam., bears N. 6° E., 69 lks. dist., with healed blaze.

A fir, 45 ins. diam., bears S. 77 $\frac{1}{4}$ ° E., 56 lks. dist., with healed blaze.

A fir, 73 ins. diam., bears S. 9 3/4° W., 154 lks. dist., with healed blaze.

Ascend 2 ft. over SW. slope.

12.65 Spur, slopes S. 15° E.; desc. 20 ft. over SE. slope.

14.00 Ravine, drains S.; asc. 205 ft. over SW. slope.

33.30 Spur, slopes S.; desc. 195 ft. over SE. slope.

38.50 Head of ravine, drains S.; asc. 25 ft. over SW. slope.

40.40 The $\frac{1}{4}$ sec. cor. of sec. 36 only, T. 20 S., R. 9 W., monumented with an iron post, 1 in. diam., extending 8 ins. above solid rock, firmly set in a drill hole, with brass cap marked

$\frac{1}{4}$ S 36
1954

from which the original bearing trees

The root hole of a fallen and burned fir, 48 ins. diam., bears N. 52 $\frac{1}{2}$ ° W., 46 lks. dist., with a burned blaze.

The root hole of a fallen and burned fir, 48 ins. diam., bears S. 89° E., 29 lks. dist., with a burned bark blaze.

and bearing trees marked by Tillman in 1954.

A fir, 31 ins. diam., bears N. 9 3/4° E., 72 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A fir, 10 ins. diam., bears N. 70 $\frac{1}{2}$ ° W., 26 lks. dist., with healed blaze.

N. 83° 01' E., beginning new measurement.

Descend 30 ft. over SE. slope.