

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy., T. 21 S., R. 9 W.

CHAINS

- 1.10 Creek, 1 lk. wide, course S.; asc. 175 ft. over SW. slope.
- 10.47 Point for the $\frac{1}{4}$ sec. cor. of sec. 1 only, T. 21 S., R. 9 W.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked
- $\frac{1}{4}$ S 1
 T 21 S R 9 W
 1967
- from which
- A fir, 21 ins. diam., bears S. 51° E., $36\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S1 BT.
- A fir, 28 ins. diam., bears S. 62° W., 72 lks. dist., mkd. $\frac{1}{4}$ S1 BT.
- Ascend 155 ft. over SW. slope.
- 27.70 Ridge, bears N. 60° W. and S. 60° E.; asc. 40 ft. along N. slope.
- 32.20 Spur, slopes N. 10° E.; desc. 205 ft. over NE. slope.
- 36.70 Head of ravine, drains N.; asc. 10 ft. along N. slope.
- 39.30 Spur, slopes NE.; desc. 395 ft. over SE. slope.
- 49.80 Creek, 2 lks. wide, course N. 40° E.; asc. 50 ft. over NW. slope.
- 51.42 The closing cor. of Tps. 20 and 21 S., R. 9 W., hereinbefore desc.
From this point the $\frac{1}{4}$ sec. cor. of sec. 31 only, on the W. bdy. of T. 20 S., R. 8 W., bears N. $1^\circ 23'$ E., 1.02 chs. dist.
- Land, mountainous.
Soil, rocky clay loam.
Timber, fir, hemlock, cedar, maple, and alder; undergrowth, vine maple, arrowwood, hazel, huckleberry, salmonberry, rhododendron, thimbleberry, and salal.
-
- Dependent Resurvey of a Portion of the Subdivisional Lines, T. 21 S., R. 9 W., Willamette Meridian, Oregon
- (Restoring the 1877 survey by William Thiel,
the 1879 survey by F. M. Johnson, and the
1894 survey by Alonzo Gesner)
-
- From the cor. of secs. 13, 14, 23, and 24, determined at record bearing and distance from the remains of the original bearing trees:
- A stump hole, bears N. 48° E., 13 lks. dist.
- The stump hole of a fallen and decayed hemlock, 12 ins. diam., bears S. 71° E., 20 lks. dist., with no marks remaining.
- The stump hole of a fallen and decayed hemlock, 12 ins. diam., bears S. 68° W., 27 lks. dist., with no marks remaining.
- A sawed fir stump, 60 ins. diam., bears N. 55° W., 29 lks. dist. with axe marks visible on remaining bottom portion of old blaze.
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked