

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy., T. 21 S., R. 9 W.

CHAINS

T 21 S R 9 W
 S 14 | S 13
 S 23 | S 24
 1966

FD OK
 3/96 Clyde Mulkins
 M123-67

from which

A fir, 4 ins. diam., bears N. 80° E., 66 lks. dist., mkd. T21S R9W S13 BT.

A fir, 4 ins. diam., bears S. 40½° E., 17 lks. dist., mkd. T21S R9W S24 BT.

An alder, 9 ins. diam., bears S. 66° W., 39 lks. dist., mkd. T21S R9W S23 BT.

A fir, 4 ins. diam., bears N. 17½° W., 131 lks. dist., mkd. T21S R9W S14 BT.

N 89° 18' E., bet. secs. 13 and 24, marking and blazing the true line.

Ascend 475 ft. over NW. slope, changing to W. slope, through logged area and dense young timber.

14.60 Dirt road, 20 lks. wide, bears N. 30° W. and S. 30° E.

22.25 Dirt road, 20 lks. wide, bears N. 35° W. and S. 35° E.

28.80 Ridge, bears N. 20° E. and S. 20° W.; desc. 235 ft. over SE. slope.

36.70 Head of ravine, drains S.; asc. 35 ft. over SW. slope.

38.75 Spur, slopes S. 45° E.; desc. 75 ft. over E. slope.

40.08 The ¼ sec. cor. of secs. 13 and 24, determined at record bearing and distance from the original bearing trees:

A sawed fir stump, 50 ins. diam., bears N. 8½° E., 41 lks. dist. with opened and burned blaze.

A stump hole, bears S. 49½° E., 50 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked

¼ S 13
 S 24
 T 21 S R 9 W
 1966

from which

A fir, 4 ins. diam., bears N. 41° W., 23 lks. dist., mkd. X BT.

A fir, 6 ins. diam., bears S. 6½° W., 40 lks. dist., mkd. ¼ S24 BT.

S. 89° 52' E., beginning new measurement.

Descend 100 ft. over E. slope.

2.40 Bottom of descent, slopes SE.; asc. 25 ft. over SW. slope.

4.80 Spur, slopes S.; desc. 280 ft. over SE. slope.

11.50 Creek, 3 lks. wide, course S.; asc. 480 ft. over SW. slope.