

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 21 S., R. 9 W.

CHAINS	
75.70	Top of ascent, slopes W.; desc. 90 ft. over NW. slope.
79.02	The cor. of secs. 11, 12, 13, and 14, determined at record bearing and distance from the original bearing trees:
	A hemlock snag, 13 ins. diam., bears N. 32° E., 22 lks. dist., with opened and decayed blaze.
	A decayed hemlock stump, 14 ins. diam., bears S. 32½° E., 25 lks. dist., with no marks remaining.
	A decayed fir stump, 60 ins. diam., bears S. 78° W., 76 lks. dist., with no marks remaining.
	A hemlock snag, 20 ins. diam., bears N. 10° W., 45 lks. dist., with scribe marks T21S visible on opened blaze.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap marked
	T 21 S R 9 W S 11 S 12 S 14 S 13 1966
	from which new bearing trees
	A hemlock, 6 ins. diam., bears N. 40° E., 24 lks. dist., mkd. T21S R9W S12 BT.
	A fir, 6 ins. diam., bears S. 50° E., 9 lks. dist., mkd. T21S R9W S13 BT.
	A fir, 5 ins. diam., bears S. 45° W., 17 lks. dist., mkd. T21S R9W S14 BT.
	A hemlock, 5 ins. diam., bears N. 25° W., 34 lks. dist., mkd. T21S R9W S11 BT.
	Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, maple, alder, and willow; undergrowth, salmonberry, thimbleberry, arrowwood, vine maple, huckleberry, hazel, ceanothus, salal, and fern.
	S. 89° 42' E., bet. secs. 12 and 13.
	Descend 25 ft. over NE. slope, through dense young timber.
3.10	Creek, 4 lks. wide, course N. 60° W.; asc. 125 ft. over SW. slope, changing to W. slope.
6.60	Dirt road, 20 lks. wide, bears N. 55° W. and S. 55° E., curving to E.
17.50	Top of ascent, slopes N.; desc. 10 ft. over NE. slope.
19.40	Ravine, drains N. 65° W.; asc. 225 ft. over SW. slope, changing to W. slope.
31.50	Same dirt road, 20 lks. wide, bears N. and S.
36.90	Same dirt road, 20 lks. wide, bears NW. and SE.
40.32	Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist. there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked