

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines. T. 21 S., R. 9 W.

CHAINS

A fir snag, 16 ins. diam., bears N. 15° E., 24 lks. dist., with scribe marks SBT visible on opened blaze.

The stump hole of a fallen fir, 28 ins. diam., bears N. 49° W., 7 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \hline S\ 11\ | \ S\ 12 \\ T\ 21\ S\ | \ R\ 9\ W \\ 1966 \end{array}$$

Ed. O.K. Les Roberts  
 PLS 1059  
 For: L.A. Paper Co  
 8/19/85  
 CS 63/18  
 M 99-32

from which new bearing trees

A fir, 6 ins. diam., bears N. 62° E., 28 lks. dist., mkd. ¼ S12 BT.

A fir, 6 ins. diam., bears S. 44° W., 16 lks. dist., mkd. ¼ S11 BT.

N. 1° 12' E., beginning new measurement.

Ascend 15 ft. over SW. slope.

3.20 Top of ascent, slopes W.; desc. 45 ft. over N. slope.

4.50 Creek, 2 lks. wide, course N. 40° W.; asc. 60 ft. over SW. slope.

8.40 Spur, slopes W.; desc. 15 ft. over NW. slope.

10.40 Bottom of descent, slopes W.; asc. 70 ft. over SW. slope.

21.10 Top of ascent, slopes W.; desc. 270 ft. over NW. slope; enter area of the Oxbow Burn.

35.10 Creek, 4 lks. wide, course W.; asc. 150 ft. over S. slope.

38.18 The cor. of secs. 1, 2, 11, and 12, determined at record bearing and distance from the remains of the original bearing trees:

A fir root crown, 14 ins. diam., bears N. 28° E., 14 lks. dist., with no marks remaining.

A rotted and burned fir stump, 18 ins. diam., bears S. 87° W., 33 lks. dist., with scribe marks T21S R9W S11 BT visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

$$\begin{array}{c} T\ 21\ S\ R\ 9\ W \\ \hline S\ 2\ | \ S\ 1 \\ \hline S\ 11\ | \ S\ 12 \\ 1966 \end{array}$$

from which

A fir, 6 ins. diam., bears N. 3° E., 89 lks. dist., mkd. T21S R9W S1 BT.

A fir, 6 ins. diam., bears S. 8° E., 101 lks. dist., mkd. T21S R9W S12 BT.

A fir, 11 ins. diam., bears S. 34° W., 83 lks. dist., mkd. T21S R9W S11 BT.