

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 21 S., R. 9 W.

CHAINS

- 9.30 Top of ascent, slopes W.; desc. 15 ft. along W. slope.
- 14.50 Bottom of descent, slopes W.; asc. 20 ft. along W. slope.
- 29.40 Spur, slopes W.; desc. 250 ft. over NW. slope.
- 34.60 Creek, 8 lks. wide, course W.; asc. 175 ft. over SW. slope.
- 40.30 The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, determined at record bearing and distance from the original bearing trees:
- A fir snag, 12 ins. diam., bears S. 85° E., 9 lks. dist., with scribe marks $\frac{1}{4}$ S visible on opened blaze.
- A fir snag, 15 ins. diam., bears S. 67° W., 11 lks. dist., with scribe marks BT visible on opened blaze.
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ diam., 24 ins. in the ground, with brass cap marked
- FD. OK 12-90
M 111 - 29

S	$\frac{1}{4}$	S	1
T	21	S	R 9 W
1967			
- from which new bearing trees
- A fir, 28 ins. diam., bears S. 54° E., 23 lks. dist., mkd. $\frac{1}{4}$ S1 BT.
- A fir, 8 ins. diam., bears N. 24° W., 33 lks. dist., mkd. $\frac{1}{4}$ S2 BT.
-
- N. $0^\circ 54'$ E., beginning new measurement.
- Ascend 35 ft. over SW. slope.
- 2.50 Spur, slopes SW.; desc. 15 ft. over NW. slope.
- 3.55 Ravine, drains SW.; asc. 170 ft. over SE. slope, changing to SW. slope.
- 17.50 Top of ascent, slopes W.; desc. 10 ft. over NW. slope.
- 19.90 Point for the N $1/16$ sec. cor. of secs. 1 and 2.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap marked
- | | |
|------|---------------------|
| N | $1/16$ |
| S | $2 \frac{1}{4}$ S 1 |
| 1967 | |
- from which
- A fir, 18 ins. diam., bears N. 46° E., 17 lks. dist., mkd. N $1/16$ S1 BT.
- A hemlock, 8 ins. diam., bears S. $46\frac{1}{2}^\circ$ W., 11 lks. dist., mkd. N $1/16$ S2 BT.
- Descend 375 ft. over NW. slope.
- 30.30 Creek, 8 lks. wide, course W.; asc. 315 ft. over S. slope.
- 39.80 Point for the $1/16$ -80 cor of secs. 1 and 2.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap marked