

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines. T. 21 S., R. 9 W.

CHAINS

$$\begin{array}{c} 1/16 \\ S 2 | S 1 \\ 80 \\ 1967 \end{array}$$

from which

A fir, 56 ins. diam., bears N. 85° E., 53 lks. dist., mkd. 1/16-80 S1 BT.

A fir, 28 ins. diam., bears S. 75° W., 25 lks. dist., mkd. 1/16-80 S2 BT.

Ascend 155 ft. over SW. slope.

50.40 Spur, slopes SW.; desc. 135 ft. over NW. slope.

59.70 Point for the 1/16-100 cor. of secs. 1 and 2.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

$$\begin{array}{c} 1/16 \\ S 2 | S 1 \\ 100 \\ 1967 \end{array}$$

from which

A hemlock, 13 ins. diam., bears S. 59° E., 62 lks. dist., mkd. 1/16-100 S1 BT.

A fir, 62 ins. diam., bears S. 27° W., 71 lks. dist., mkd. 1/16-100 S2 BT.

Descend 85 ft. over NW. slope.

62.00 Creek, 4 lks. wide, course S. 70° W.; asc. 40 ft. over SW. slope.

63.50 Spur, slopes SW.; desc. 10 ft. over NW. slope.

64.70 Creek, 2 lks. wide, course SW.; asc. 160 ft. over S. slope.

69.16 The closing cor. of secs. 1 and 2, on the S. bdy. of sec. 36, T. 20 S., R. 9 W., hereinbefore described.

From this point the cor. of secs. 35 and 36 only, T. 20 S., R. 9 W., bears S. 89° 00' W., 12.44 chs. dist.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, maple, and lader; undergrowth, vine

maple, arrowwood, huckleberry, hazel, thimbleberry, salmonberry, salal, and fern.

From the ¼ sec. cor. of secs. 22 and 23, occupied by the original corner tree, a fir, 20 ins. diam., with scribe marks ¼ S visible on opened blaze, on W. side, from which the original bearing trees:

A decayed fir stump, 10 ins. diam., bears N. 53° E., 17 lks. dist., with no marks remaining.

A decayed fir stump, 18 ins. diam., bears S. 45° W., 10 lks. dist., with no marks remaining.

and a monument for which I have no record:

An iron pipe, 2 ins. diam., extending 24 ins. above ground, firmly set, bears S., 3 lks. dist., with steel cap marked ¼ S 22 23.