

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 21 S., R. 9 W.

CHAINS	
	From the corner of secs. 11, 12, 13 and 14.
	S. 88° 12' W., bet. secs. 11 and 14
	Descend 135 ft. over N.W. slope, through heavy young timber and dense undergrowth.
4.65	Dirt Road, 15 lks. wide, bears N. 30° E. and S. 30° W.
19.10	Same dirt road, 20 lks. wide, bears N.W. and S.E.
19.51	Point for the E 1/16 sec. cor. of secs. 11 and 14.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked
	$E \frac{1}{16} \frac{S \ 11}{S \ 14}$ 1966
	from which
	A fir, 12 ins. diam., bears N. 68° E., 112 lks. dist., mkd. E 1/16 S11 BT.
	A fir, 8 ins. diam., bears S. 51° E., 17 lks. dist., mkd. E 1/16 S14 BT.
	Descend 65 ft. over NW. slope
23.75	Scare Creek, 5 lks. wide, course N. 15° W.; asc. 420 ft. over E. slope.
39.02	Point for the ¼ sec. cor. of secs. 11 and 14 at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked.
	$\frac{1}{4} \frac{S \ 11}{S \ 14}$ T 21 S R 9 W 1966
	from which
	A fir, 8 ins. diam., bears N. 59° W., 16 lks. dist., mkd. ¼ S11 BT.
	A fir, 6 ins. diam., bears S. 42° E., 23 lks. dist., mkd. ¼ S14 BT.
	Ascend 200 ft. over E. slope.
40.00	Dirt road, 30 lks. wide, bears N. and S.
43.55	Ridge, bears N. 15° E. and S. 15° W.; desc. 545 ft. over SW. slope.
59.50	Ravine, drains S. 35° W.; asc. 60 ft. over SE. slope.
61.90	Spur, slopes S.; desc. 55 ft. over SW. slope.
64.00	Ravine, drains S.; asc. 70 ft. over SE. slope.
66.45	Top of ascent, slopes S.; desc. 70 ft. over SW. slope.
72.40	Ravine, drains S.; asc. 130 ft. over SE. slope, changing to NE. slope.

FUCK  
C. MURKIN  
3/23/67