

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 21 S., 9 W.

## CHAINS

from which

A hemlock, 8 ins. diam., bears N. 83\* E., 129 lks.  
dist., mkd. S 1/16 S2 BT.

A fir, 35 ins. diam., bears N. 69\* W., 161 lks.  
dist., mkd. S 1/16 S3 BT.

Ascend 50 ft. over SW. slope.

- 20.50 Enter area of the Oxbow Burn and heavy timber, edge  
bears NE. and W.
- 24.30 Top of ascent, slopes W.; desc. 35 ft. over NW. slope.
- 34.00 Bottom of descent, slopes W.; asc. 15 ft. over SW. slope.
- 40.20 The  $\frac{1}{4}$  sec. cor. of secs. 2 and 3, monumented with an  
iron post, 2 $\frac{1}{2}$  ins. diam., projecting 4 ins. above ground,  
firmly set, with brass cap marked and witnessed as  
described in the official record of the 1963 remonumentation.

---

N. 0\* 09' W., beginning new measurement.

Ascend 55 ft. over SW. slope.

- 6.10 Ridge, bears NW. and SE.; desc. 285 ft. over NW. slope,  
changing to NE. slope.
- 17.60 Creek, 3 lks. wide, course N. 70\* E.; asc. 65 ft. over  
SE. slope.
- 21.10 Spur, slopes NE.; desc. 265 ft. over NW. slope.
- 26.90 Scare Creek, 25 lks. wide, course N. 80\* W.; asc. 85 ft.  
over SW. slope.
- 36.90 Top of ascent, slopes W.; desc. 25 ft. over NW. slope.
- 37.50 Creek, 1 lk. wide, course S. 70\* W.; asc. 255 ft. over  
general SW. slope.
- 68.80 Intersect the S. bdy. of T. 20 S., R. 9 W.

True point for the closing cor. of secs. 2 and 3.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins.  
in the ground, with brass cap marked.

T 20 S R 9 W  
S 35  
S 3 | S 2  
T 21 S R 9 W  
CC  
1967

from which

A fir, 55 ins. diam., bears S 13 $\frac{1}{2}$ \* E., 61 lks.  
dist., with healed blaze. (original bearing  
tree)

A fir snag, 55 ins. diam., bears S. 32\* W., 92  
lks. dist., with healed blaze. (original  
bearing tree)