

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 21 S., R. 9 W.

CHAINS

with no marks visible.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked
$$\frac{1}{4} \begin{array}{l} \underline{S 15} \\ S 22 \end{array}$$

T 21 S R 9 W
1966

from which a new bearing tree

A fir, 8 ins. diam., bears S. 62° E., 12 lks. dist., mkd. $\frac{1}{4}$ S22 BT.

Deposit the original stone alongside the iron post.

N. 89° 47' W., beginning new measurement.

Descend 15 ft. over NW. slope.

1.40 Creek, 1 lk. wide, course S. 80° W.; asc. 10 ft over SE. slope.

3.50 Spur, slopes SW.; desc. 90 ft. over SW. slope.

6.75 Hard surfaces road, 30 lks. wide, bears N. 30° W. and S. 30° E.20.70 Vincent Creek, 10 lks. wide, course N. 35° W.; asc. 190 ft. over NE. slope.

27.40 Spur, slopes N.; desc. 170 ft. over NW. slope.

33.50 Creek, 8 lks. wide, course N. 60° E.; asc. 165 ft. over SE. slope.

39.65 The cor. of secs. 15, 16, 21, and 22, determined at record bearing and distance from the original bearing trees:

The stump hole of a fallen and decayed fir,
35 ins. diam., bears N. $15\frac{1}{2}^{\circ}$ E., 57 lks.
dist., with no marks visible.A fir, 38 ins. diam., bears N. 32° W., 17 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked
$$\begin{array}{c} T 21 S R 9 W \\ \underline{S 16 | S 15} \\ \underline{S 21 | S 22} \\ 1966 \end{array}$$

From which new bearing trees

A cedar, 30 ins. diam., bears N. 73° E., 42 lks.
dist., mkd. T21 S R9W S15 BT.A fir, 10 ins. diam., bears S. $18\frac{1}{2}^{\circ}$ E., 56 lks.
dist., mkd. T21S R9W S22 BT.