

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 21 S., R. 9 W.

CHAINS	Timber, fir, hemlock, cedar, maple, and alder; undergrowth, huckleberry, thimbleberry, arrowwood, salmonberry, wine maple, rhododendron, hazel, blackberry, salal, Oregon grape, and fern.
	N. 0° 05' E., bet. secs. 9 and 10.
	Ascend 50 ft. over SE. slope, through heavy timber and dense undergrowth.
1.50	Spur, slopes E.; desc. 370 ft. over NE. slope.
9.10	Creek, 10 lks. wide, course N. 75° E.; asc. 70 ft. over SE. slope.
11.25	Gravelled road, 30 lks. wide, bears N. 70° E. and S. 70° W.
16.10	Top of ascent, slopes E.; desc. 60 ft. over NE. slope.
18.70	Creek, 5 lks wide, course S. 60° E.; asc. 265 ft. over S. slope.
39.62	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{8}$ ins. diam., 24 ins. in the ground, with brass cap marked
	$\begin{array}{c} \frac{1}{4} \\ S\ 9\ \frac{1}{4}\ S\ 10 \\ T\ 21\ S\ R\ 9\ W \\ 1966 \end{array}$
	<i>Find. O.K. by L. ROBERTS NOV. 1981 M 90-13 FND. 014 12-90 M 111 - 27</i>
	from which
	A fir, 18 ins. diam. bears S. 34° E., 33 lks. dist., mkd. $\frac{1}{4}$ S10 BT.
	A fir, 16 ins. diam., bears S. 14° W., 11 lks. dist., mkd. $\frac{1}{4}$ S9 BT.
	Ascend 310 ft. over S. slope.
77.15	Ridge, bears N. 80° W. and S. 80° E.; desc. 75 ft over N. slope.
79.00	Point for the 1/16-80 cor. of sec. 9 only, at proportionate distance between the closing cor. of secs. 4 and 9 and the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.
	Set an iron post, 28 ins. long, $2\frac{1}{8}$ ins. diam., 22 ins. in the ground, with brass cap marked
	$\begin{array}{c} \frac{1}{16} \\ S\ 9\   \\ 80 \\ 1966 \end{array}$
	<i>Find. O.K. by L. ROBERTS Nov. 1981 M 90-13</i>
	from which
	A hemlock, 10 ins. diam., bears N. 89° W., 36 lks. dist., mkd. 1/16-80 S9 BT.
	A hemlock, 6 ins. diam., bears S. 48° W., 46 lks. dist., mkd. 1/16-80 S9 BT.