County Surveyor's Record, Douglas County, Oregon

CHAINS

Descend 8 ft. over N. slope.

79.24 Point for the cor. of secs. 3 and 10 only, at proportionate distance, in latitude, and at record distance in departure, from the $\frac{1}{4}$ sec. cor. of secs. 3 and 10; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked

FD. OK 12-90
MIII - 27

T 21 S | R 9 W
S 9 | S 3
S 10
1966

from which

A fir, 31 ins. diam., bears N. $49\frac{1}{2}$* E., 54 lks. dist.,mkd. T21S R9W S3 BT.

A hemlock, 12 ins. diam., bears S. 45* E., 9 lks. dist., mkd. T21S R9W S10 BT.

Land, mountainous.
Soil, sandy clay loam.
Timber, fir, hemlock, cedar, maple, alder, willow, and dogwood; undergrowth, huckleberry, arrowwood, vine maple, salmonberry, thimbleberry, hazel, Oregon grape, salal, and fern.

From the cor. of secs. 2, 3, 10, and 11.

N. 87* 47' W., bet. secs. 3 and 10.

Descend 345 ft. over NW. slope, through heavy timber and dense undergrowth.

19.30 Dirt road, 25 lks. wide, bears N. 50* E. and S. 50* W.

28.30 Hard surfaced road, 30 lks. wide, bears N. 30* W. and S. 30* E.

30.10 Vincent Creek, 30 lks. wide, course N.; asc. 130 ft. over NE. slope.

31.50 Spur, slopes N. 50* E.; desc. 30 ft. over NW. slope.

32.60 Ravine, drains N. 50* E.; asc. 80 ft. over NE. slope.

39.15 The $\frac{1}{4}$ sec. cor. of secs. 3 and 10, determined at record bearing and distance from the original bearing trees:

A fir, 65 ins. diam., bears N. 49* E., 16 lks. dist., with healed blaze.

A cedar, 18 ins. diam., bears S. 15* E., 46 lks. dist., with no marks visible on partially opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

$\frac{1}{4}$ S 3
S 10
T 21 S R 9 W
1966