

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 21 S., R. 9 W.

CHAINS

39.62

The $\frac{1}{4}$ sec. cor. of sec. 3 only, determined at record distance from the original bearing trees:

A fir, 56 ins. diam., bears N. $68\frac{1}{2}^*$ E., 39 lks. dist., with fragmentary scribe marks visible on opened blaze.

A fir, 56 ins. diam., bears N. 37^* W., 53 lks. dist., with healed blaze. (Record, N. 32^* W.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{8}$ ins. diam., 24 ins. in the ground, with brass cap marked

*FWD OK
12-90 M111-61*

$\frac{1}{4}$
T 21 S
S 3
R 9 W
1966

from which a new bearing tree

A hemlock, 12 ins. diam., bears S. 44^* E., 60 lks. dist., mkd. $\frac{1}{4}$ S3 BT.

N. 0^* $03'$ E., beginning new measurement.

5.00

Creek, 2 lks. wide, course NW.; asc. 15 ft. over SW. slope.

6.25

Top of ascent, slopes W.; desc. 20 ft. over NW. slope.

7.85

Ravine, drains W.; asc. 85 ft. over SW. slope.

11.60

Spur, slopes W.; desc. 2 ft. over N. slope.

11.71

Point for the S $\frac{1}{16}$ sec. cor. of sec. 4 only.

Set an iron post, 28 ins. long, $2\frac{1}{8}$ ins. diam., 24 ins. in the ground, with brass cap marked

S $\frac{1}{16}$
S 4
1966

from which

A hemlock, 10 ins. diam., bears N. 74^* W., 36 lks. dist., mkd. S $\frac{1}{16}$ S4 BT.

A hemlock, 10 ins. diam., bears S. 80^* W., $7\frac{1}{2}$ lks. dist., mkd. S $\frac{1}{16}$ S4 BT.

Descend 145 ft. over N. slope.

15.10

Creek, 4 lks. wide, course N. 85^* E., asc. 60 ft. over SE. slope.

18.35

Spur, slopes E.; desc. 170 ft. over NE. slope.

27.00

Vincent Creek, 80 lks. wide, course N. 15^* W.; desc. 8 ft along right bank of creek.

31.33

Point for the $\frac{1}{4}$ sec. cor. of sec. 4 only.

Set an iron post, 28 ins. long, $2\frac{1}{8}$ ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to