

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 21 S., R. 9 W.

## CHAINS

From the cor. of secs. 28, 29, 32, and 33, determined at record bearing and distance from the original bearing trees:

A decayed fir stump, 20 ins. diam., bears N. 18\* E., 80 lks. dist., with no marks remaining.

A maple, 22 ins. diam., bears S. 73 $\frac{1}{4}$ \* E., 79 lks. dist., with scribe marks S3 visible on opened blaze.

A maple crown, 20 ins. diam., bears S. 36 $\frac{1}{2}$ \* W., 10 lks. dist., with no marks remaining.

A fir, 88 ins. diam., bears N. 33  $\frac{3}{4}$ \* W., 57 lks. dist., with no marks visible on partially opened blaze. (Slope dist., 65 lks. record, 65 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{8}$  ins. diam., 25 ins. in the ground, with brass cap marked

T 21 S R 9 W  
 S 29 | S 28  
 S 32 | S 33  
 1966

from which new bearing trees

A fir, 11 ins. diam., bears N. 47\* E., 99 lks. dist., mkd. T21S R9W S28 BT.

A maple, 35 ins. diam., bears S 33\* W., 61 lks. dist., mkd. T21S R9W S32 BT.

N. 0\* 17' W., bet secs. 28 and 29.

Ascend 325 ft. over broken SE. slope, through heavy timber and dense undergrowth.

10.75 Spur, slopes E.; desc. 245 ft. over NE. slope.

18.60 Bottom of descent, slopes SE.; asc. 95 ft over S. slope.

25.40 Spur, slopes E.; desc. 80 ft. over NE. slope.

29.60 Bottom of descent, slopes E.; asc. 15 ft. along E. slope.

35.60 Top of ascent, slopes E.; desc. 105 ft. over N slope.

39.35 Creek, 5 lks. wide, course E.; asc. 5 ft. over S. slope.

39.53 The  $\frac{1}{4}$  sec. cor. of secs. 28 and 29, remonumented by Milo E. Godfrey, Deputy County Surveyor, in 1964, with an iron post, 1 $\frac{1}{8}$  ins. diam., extending 20 ins. above ground, firmly set. with brass cap marked

COUNTY SURVEYORS OFFICE  
 T 21 S  
 S | S  
 29 | 28  
 R 9 W  
 1964

from which the only remaining original bearing tree: