

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 21 S., R. 9 W.

CHAINS

A rotted white fir stub, 18 ins. diam., bears N. 77 1/2* E., 23 lks. dist., with old axe marks visible on decayed blaze.

and bearing trees marked by Godfrey

A fir, 20 ins. diam., bears N. 53 1/4* E., 50 lks. dist., with scribe marks 1/4 S28 CS BT visible on open double blaze.

A hemlock, 36 ins. diam., bears S. 48 1/2* W., 88 lks. dist., with scribe marks 1/4 S29 CS BT visible on open double blaze.

N. 0* 14' E., beginning new measurement.

Ascend 65 ft. over S. slope.

- 1.60 Spur, slopes E.; asc. 15 ft. along E. slope.
- 9.50 Top of ascent, slopes E.; desc. 125 ft. over NE. slope.
- 10.90 Dirt road, 15 lks. wide, bears E. and W.
- 17.30 Creek, 5 lks. wide, course N. 50* E.; asc. 265 ft. over SE. slope.
- 39.71 Point for the cor. of secs. 20, 21, 28, and 29, at proportionate distance; there is no remaining evidence of the original corner. This point falls in dirt road, 25 lks. wide, which bears N. 40* E. and S. 40* W.

Set an iron post, 28 ins. long, 2 1/2 ins diam., 40 ins. in the ground, the top 12 ins. below the road surface, with brass cap marked

T 21 S R 9 W
S 20 S 21
S 29 S 28
1966

FDOK
12/2000
Smithers
CS 65/33-27

from which

An alder, 5 ins. diam., bears N. 16 1/2* E., 68 lks. dist., mkd. T21S R9W S21 BT.

A fir, 5 ins diam., bears S. 61* E., 126 lks. dist., mkd. T21S R9W S28 BT.

A hemlock, 12 ins. diam., bears S. 27 1/4* W., 246 lks. dist., mkd. T21S R9W S29 BT.

A fir, 5 ins. diam., bears N. 49 1/2* W., 136 lks. dist., mkd. T21S R9W S20 BT.

Land, mountainous.
Soil, sandy clay loam.
Timber, fir, hemlock, cedar, maple, alder, and willow; undergrowth, salmonberry, vine maple, huckleberry, blackberry, thimbleberry, hazel, arrowwood, Oregon grape, salal, and fern.

From the 1/4 sec. cor. of secs. 21 and 28, determined at record bearing and distance from the original bearing trees:

A sawed hemlock stump, 38 ins. diam., bears