

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 21 S., R. 9 W.

CHAINS

S. 89\* 22' W., beginning new measurement.  
 Ascend 105 ft. over NE. slope.  
 6.40 Spur, slopes N.; desc. 45 ft. over NW. slope.  
 8.00 Ravine, drains N.; asc. 405 ft. over general NE. slope.  
 30.70 Ridge, bears N. and S.; desc. 260 ft. over NW. slope.  
 37.00 Ravine, drains N. 20\* W.; asc. 90 ft. over NE. slope.  
 39.19 The cor. of secs. 8, 9, 16, and 17.

Land, mountainous.  
 Soil, sandy clay loam.  
 Timber, fir, hemlock, cedar, maple, alder, and yew;  
 undergrowth, vine maple, huckleberry, salmonberry, arrowwood,  
 hazel, poison oak, thimbleberry, Oregon grape, salal, and fern.

From the cor. of secs. 4 and 5 only, on the N. bdy. of sec. 8,  
 monumented with the original sandstone, 40 x 24 x 12 ins.,  
 extending 12 ins. above ground, firmly set, marked with 4  
 grooves on E. face, from which the original bearing trees:

A fir, 70 ins. diam., bears S. 46\* E., 124 lks.  
 dist., with healed blaze. (Record, S. 41\* E.)

A fir, 35 ins. diam., bears S. 87\* W., 60 lks.  
 dist., with fragmentary scribe marks visible  
 on partially healed blaze. (Record, S. 83\* W.,  
 66 lks.)

A fir snag, 58 ins. diam., bears N. 43\* W.,  
 135 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.  
 in the ground, with brass cap marked

T 21 S R 9 W  
 S 5 | S 4  
 S 8  
 1966

from which new bearing trees

A fir, 16 ins. diam., bears N. 71\* E., 8 lks.  
 dist., mkd. T21S R9W S4 BT.

A fir, 18 ins. diam., bears N. 39\* W., 36 lks.  
 dist., mkd. T21S R9W S5 BT.

Deposit the original sandstone alongside the  
 iron post.

S. 89\* 20' E., on the S. bdy. of sec. 4.

Ascend 230 ft. over SW. slope, through heavy timber and  
 dense undergrowth.

6.25 Spur, slopes N. 60\* W.; desc. 100 ft. over NE. slope.

*Fd. OK. by:  
 Les Roberts  
 Dec. 1982  
 M 90-30*