

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 21 S., R. 9 W.

CHAINS	
10.00	Bottom of descent, slopes N.; asc. 170 ft. over NW. slope.
15.60	Ridge, bears N. 40* E. and S. 40* W.; desc. 270 ft. over SE. slope.
26.83	The closing cor. of secs. 8 and 9, determined at record bearing and distance from the only remaining original bearing tree: A fir, 66 ins. diam., bears S. 65 ¹ / ₂ * E., 160 lks. dist., with healed blaze. At the corner point Set an iron post, 28 ins. long, 2 ¹ / ₂ ins. diam., 24 ins. in the ground, with brass cap marked <div style="text-align: center;"> $\begin{array}{c} \underline{S\ 4} \\ S\ 8\ \ S\ 9 \\ C\ \ C \\ T\ 21\ S\ R\ 9\ W \\ 1966 \end{array}$ </div> from which new bearing trees A cedar, 15 ins. diam., bears S. 11* E., 41 lks. dist., mkd. T21S R9W S9 CC BT. A fir, 20 ins. diam., bears S. 80* W., 23 lks. dist., mkd. T21S R9W S8 CC BT. Descend 305 ft. over SE. slope, changing to NE. slope.
37.00	Buck Creek, 6 lks. wide, course N.; asc. 105 ft. over NW. slope.
39.39	The ¹ / ₄ sec. cor. of sec. 4 only, monumented with a sandstone, not of record, 14 x 12 x 8 ins., extending 8 ins. above ground, firmly set, marked CS on S. face, from which the original bearing trees: A fir, 38 ins. diam., bears N. 58* E., 44 lks. dist., with scribe marks BT visible on opened blaze. A maple, 27 ins. diam., bears S. 20* E., 83 lks. dist., with no marks remaining on opened and rotted blaze. (Record, S. 12* E., 75 lks. And a bearing tree not of record A fir, 30 ins. diam., bears S. 24 ¹ / ₂ * E., 18 lks. dist., with healed blaze. At the corner point Set an iron post, 28 ins. long, 2 ¹ / ₂ ins. diam., 22 ins. in the ground, with brass cap marked <div style="text-align: center;"> $\begin{array}{c} T\ 21\ S\ R\ 9\ W \\ \underline{\frac{1}{4}\ S\ 4} \\ 1966 \end{array}$ </div> from which a new bearing tree A fir, 48 ins. diam., bears N. 15* W., 60 lks. dist., mkd. ¹ / ₄ S4 BT. The corner is located on the point of a spur, slopes SW.