

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 21 S., R. 9 W.

CHAINS

N. 89° 13' E., beginning new measurement.

Ascend 420 ft. over SW. slope, changing to NW. slope.

10.60 Ridge, bears N. and S.; desc. 135 ft. over general NE. slope.

19.83 Point for the E 1/16 cor. of sec. 4 only.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

E 1/16 S 4
1966

from which

A hemlock, 29 ins. diam., bears N. 20° E., 46 lks. dist., mkd. E 1/16 S4 BT.

An alder, 20 ins. diam., bears N. 17° W., 104 lks. dist., mkd. E 1/16 S4 BT.

Descend 135 ft. over NE. slope.

27.38 Point for the ¼ sec. cor. of sec. 9 only.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked

*Fnd. OK by L. ROBERTS
NOV. 1981 M 90-13*

¼ S 9
T 21 S R 9 W
1966

*FND. OK 12190
M 111-61*

from which

A hemlock, 10 ins. diam., bears S. 52° E., 43 lks. dist., mkd. ¼ S9 BT.

A hemlock, 12 ins. diam., bears S. 34° W., 59 lks. dist., mkd. ¼ S9 BT.

Descend 250 ft. over NE. slope.

39.67 Point for the 1/16-80 cor. of sec. 4 only.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

1/16 S 4 80
1966

from which

An alder, 22 ins. diam., bears N. 33° E., 59 lks. dist., mkd. 1/16-80 S4 BT.

An alder, 16 ins. diam., bears N. 4½° W., 84 lks. dist., mkd. 1/16-80 S4 BT.

Descend 20 ft. over NE. slope.

40.85 Creek, 3 lks. wide, course N. 10° E., asc. 355 ft. over NW. slope.

50.00 Spur, slopes N. 60° E.; desc. 85 ft. over SE. slope, changing to NE. slope.

59.50 Point for the 1/16-100 cor. of sec. 4 only.