

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 21 S., R. 9 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{8}$ ins. diam., 22 ins. in the ground, with brass cap marked

1/16 $\frac{S\ 4}{100}$ 1966

from which

A cedar, 6 ins. diam., bears N. 70* E., 27 lks. dist., mkd. 1/16-100 S4 BT.

A hemlock, 17 ins. diam., bears N. 1* W., 10 lks. dist., mkd. 1/16-100 S4 BT.

Descend 215 ft. over general NE. slope.

67.245

The original closing cor. of secs. 4 and 9, determined at record bearing and distance from the original bearing trees:

A fir snag, 35 ins. diam., bears S. 89* E., 30 lks. dist., with healed blaze.

The root hole of a fallen fir, 45 ins. diam., bears S. 39* W., 7 lks. dist., with no marks visible.

A fir snag, 33 ins. diam., bears N. 58* W., 22 lks. dist., with scribe marks T21 R 4 W visible on opened blaze.

67.32

Intersect the W. bdy. of sec. 3.

True point for the closing cor. of secs. 4 and 9.

Set an iron post, 28 ins. long, $2\frac{1}{8}$ ins. diam., 24 ins. in the ground, with brass cap marked

CC $\begin{array}{c} T\ 21\ S \\ S\ 4 \\ S\ 9 \\ R\ 9\ W \\ 1966 \end{array}$ S 3

*Fnd. O.K. by L. ROBERTS
NOV. 1981 M 90-13*

*FO. OK 12/90
M 111-61*

from which

A hemlock, 8 ins. diam., bears S. 39* W., 19 lks. dist., mkd. T21S R9W S9 CC BT.

A maple, 26 ins. diam., bears N. 80* W., 50 lks. dist., mkd. T21S R9W S4 CC BT.

From this point, the $\frac{1}{4}$ sec. cor. of sec. 3 only, bears N. 0* 04' W., 7.91 chs. dist., hereinbefore described.

Land, mountainous.
Soil, sandy clay loam.
Timber, fir, hemlock, cedar, maple, alder, and yew; undergrowth, vine maple, hazel, arrowwood, huckleberry, salmonberry, Oregon grape, salal, and fern.

from the cor. of secs. 8, 9, 16, and 17.

N. 0* 37' E., bet. secs. 8 and 9.

Descend 200 ft. over NE. slope, through heavy timber and dense undergrowth.

4.40

Ravine, drains N. 40* W.; asc. 5 ft. over SW. slope.