

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 21 S., R 9 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked

T 21 S R 9 W
 $\frac{S}{S} \frac{6}{7} \frac{S}{S} 5$
 1966

Fd. OK.
by: LES. Roberts
Dec 1982
M 90-30

from which new bearing trees

A hemlock, 20 ins. diam., bears N. 27° E., 26 lks. dist., mkd. T21S R9W S5 BT.A fir, 16 ins. diam., bears N. 68° W., 8 lks. dist., mkd. T21S R9W S6 BT.N. 89° $35'$ W., on the S. bdy. of sec. 6.

Ascend 165 ft. over SE. slope, through heavy timber and dense undergrowth.

4.65 Spur, slopes N. 25° E.; desc. 240 ft. over NW. slope.15.20 Ravine, drains N. 35° E.; asc. 460 ft. over SE. slope.26.45 Spur, slopes N. 15° E.; desc. 230 ft. over NW. slope.31.00 Ravine, drains N. 25° W.; asc. 150 ft. over NE. slope.

35.30 Spur, slopes N.; desc. 55 ft. over NW. slope.

37.14 The $\frac{1}{4}$ sec. cor. of sec. 6 only, monumented with the original sandstone, 14 x 12 x 8 ins., extending 6 ins. above ground, firmly set, marked $\frac{1}{4}$ on N. face, from which the only remaining original bearing tree:A fir snag, 65 ins. diam., bears S. 46° W., 40 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

T 21 S R 9 W
 $\frac{1}{4} \frac{S}{S} 6$
 1966

From which new bearing trees

A fir, 25 ins. diam., bears N. 52° E., 178 lks. dist., mkd. $\frac{1}{4}$ S6 BT.A hemlock, 28 ins. diam., bears N. 62° W., 57 lks. dist., mkd. $\frac{1}{4}$ S6BT.

Deposit the original sandstone alongside the iron post.

The corner is located at bottom of descent, slopes N.

S. 89° $58'$ W., beginning new measurement.

Ascend 95 ft. over NE. slope.