

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 21 S., R. 9 W.

CHAINS

2.50 Spur, slopes N. 25* E.; desc. 45 ft. over NW. slope.

4.10 Ravine, drains N. 10* E.; asc. 190 ft. over NE. slope.

10.00 Ridge, bears N. 10* E. and S. 50* E.; at junction with a spur, slopes SW.; desc. 365 ft. over NW. slope, changing to SW. slope.

19.42 The closing cor. of secs. 6 and 7, on the E. bdy. of sec. 12, T. 21 S., R. 10 W., hereinbefore described.

From this point, the cor. of secs. 1 and 12 only on the E. bdy. of T. 21 S., R. 10 W., bears N. 0* 35' W., 11.57 chs. dist.

Land, mountainous.
Soil, sandy clay loam.
Timber, fir, hemlock, cedar, maple, chinquapin, maple, and alder; undergrowth, vine maple, huckleberry, rhododendron, salmonberry, arrowwood, hazel, Oregon grape, salal, and fern.

The following field notes describe the remonumentation of certain original corner points, T. 21 S., R. 9 W., Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group No. 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed".

West Boundary, T. 21 S., R. 9 W.,
Willamette Meridian, Oregon

(Remonumentation of a corner established by Alonzo Gesner in 1894, and remonumented by Charles M. Collier and Fred Rodolf in 1919)

The cor. of secs. 7 and 18 only, monumented with an iron post, 2 ins. diam., extending 10 ins. above ground, firmly set, with brass cap marked

T 21 S
S 7
S 18
R 9 W
1919

from which the original bearing trees:

A maple, 21 ins. diam., bears S. 80* E., 32 lks. dist., with healed blaze. (Record, N. 80* E., 28 lks.)

A maple, 33 ins. diam., bears S. 46* E., 43 lks. dist., with healed blaze. (Record, S. 48* E.)

and a new bearing tree

A maple, 15 ins. diam., bears N. 49* E., 99 lks. dist., mkd. T21S R9W S7 BT.

Subdivision, T. 21 S., R. 9 W.,
Willamette Meridian, Oregon