

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey. Portion of Subdivisional Lines, T. 21 S., R 9 W.

CHAINS

(Remonumentation of corners established by Alonzo Gesner in 1894)

The $\frac{1}{4}$ sec. cor. of secs. 27 and 28, perpetuated by person (s) unknown, with an iron pipe, 60 ins. long, 2 ins. diam., extending 30 ins. above ground, firmly set, from which the original bearing trees:

A sawed hemlock stump, 18 ins. diam., bears S. 65* E., 35 lks. dist., with no marks remaining.

A sawed fir stump, 40 ins. diam., bears S. 70* W., 60 lks. dist., with scribe mark S visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

FD. 014 BY D. EDWARDS, JUNE 2000 - M135-6

$\frac{1}{4}$
S 28 | S 27
T 21 S R 9 W
1967

from which new bearing trees

A fir, 6 ins. diam., bears N. 42* E., 90 lks. dist., mkd. $\frac{1}{4}$ S27 BT.

A fir, 5 ins. diam., bears S. 10* W., $32\frac{1}{2}$ lks. dist., mkd $\frac{1}{4}$ s28 BT.

Deposit the iron pipe alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, determined at record bearing and distance from the original bearing trees:

A sawed fir stump, 48 ins. diam., bears N. 29* W., 19 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on opened blaze.

A sawed fir stump, 24 ins. diam., bears S. $40\frac{1}{2}$ * W., 8 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

$\frac{1}{4}$ S 22
 $\frac{1}{4}$ S 27
T 21 S R 9 W
1967

from which new bearing trees

A fir, 7 ins. diam., bears N. 42* E., 21 lks. dist., mkd. $\frac{1}{4}$ S22 BT.

A fir, 6 ins. diam., bears S. 32* E., 39 lks. dist., mkd. $\frac{1}{4}$ S27 BT.

An iron post, 2 ins. diam., extending 30 ins. above ground, loosely set, bears S. 5* E., 6 lks. dist., with steel cap marked $\frac{1}{4}$ S 22 27.