

County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certian Original Corner Points,
T. 21 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

The cor. of secs. 29, 30, 31, and 32, determined at record bearing and distance from the original bearing trees:

A fir, 42 ins. diam., bears N. 17* E. 88 lks. dist., with healed blaze.

A fir stump hole, bears S. 40* W., 5 lks. dist.

A fir, 32 ins. diam., bears N. 19* W., 24 lks. dist., with healed blaze.

At the corner point

Set a fiberglas post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

T 21 S R 9 W
S 30 S 29
S 31 S 32
1967

*Fd & Used
12/89
L. Roberts
M 109-42*

from which new bearing trees

A hemlock, 6 ins. diam., bears S. 60* E., 132 lks. dist., mkd. T21S R9W S32 BT.

A cedar, 6 ins. diam., bears S. 84* W., 65 lks. dist., mkd T21S R9W S31 BT.

The cor. of secs. 19, 20, 29, and 30, determined at record bearing and distance from the original bearing trees:

A cedar, 22 ins. diam., bears N. 18 $\frac{1}{2}$ * E., 17 lks. dist., with scribe marks S20 visible on partially healed blaze.

A fir, 23 ins. diam., bears S. 61* E., 20 lks. dist., with healed blaze.

A fir, 32 ins. diam., bears S. 12* W., 21 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{4}$ ins, diam., 24 ins. in the ground, with brass cap marked

T 21 S R 9 W
S 19 S 20
S 30 S 29
1967

from which a new bearing tree

A fir, 18 ins. diam., bears N. 85* W., 59 lks. dist., mkd. T21S R9W S19 BT.

The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, determined at record bearing from the original bearing trees:

A hemlock, 42 ins. diam., bears S. 8* E., 15 lks. dist., with fragmentary scribe marks visible on partially healed blaze. (Record, 50 lks.

*Fd. by
E.M. WOSSE
Mar. 28, 1983
SEE c.s. 58/281*