

## County Surveyor's Record, Douglas County, Oregon

T. 26 S., R. 2 W., Willamette Meridian, Oregon

## CHAINS

The history of surveys of township 26 south, range 2 west, Willamette Meridian, Oregon, in the portion covered by this resurvey is as follows:

The north and east boundaries and the subdivisional lines were surveyed by John A. McQuinn in 1883 as shown on the official plat of survey approved April 7, 1884. In 1910 Fred Mensch resurveyed the east boundary of the township as shown on the official plat of survey of township 26 south, range 1 west, approved November 11, 1911. In 1913 Charles M. Collier retraced the east boundary of the township as shown on the official plat of survey approved June 21, 1917. In 1959 Irving Zirpel, Jr. and William W. Glenn resurveyed a portion of the subdivisional lines as shown on the official plat of survey accepted August 29, 1960.

Preliminary to the resurvey the lines of the original surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were reestablished and remonumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only lines bounding, or crossing, public lands were blazed. All lines not forming a closure were measured twice.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated February 12, 1968, under Group No. 664, Oregon.

The directions of lines were determined by the solar transit method.

The geographic position of the corner of sections 12 and 13 only, on the east boundary of the township, as scaled from the Mace Mountain, Oregon, quadrangle map, published by the United States Geological Survey in 1955, is as follows:

Latitude 43° 18.9' N.      Longitude 122° 52.3' W.

The mean magnetic declination is 19° 00' E.

Dependent Resurvey, Portion of E. Bdy.,  
T. 26 S., R. 2 W., Willamette Meridian, Oregon

(Restoring the 1883 survey by John A. McQuinn, the 1910 resurvey by Fred Mensch, and the 1913 retracement by Charles M. Collier)

From the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp., rehabilitated and recored by the County Surveyor's Office in 1945 when the original weathered cornerstone, which is no longer existent, was in evidence, and subsequently perpetuated and recorded by the same office in 1966, monumented with an iron post, 1 in. diam., protruding 12 ins. above the ground, firmly set in the original mound of stone, 3 ft. base, to top, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 26 S

R 2 W  $\frac{S 12}{S 13}$  R 1 W

1966